

# Installasjonskabel

## PR, limt skjerm



### Bruksområde

|                                |                                                            |
|--------------------------------|------------------------------------------------------------|
| <b>Bruksområde</b>             | Husinstallasjonskabel til fast opplegg innen- og utendørs. |
| <b>Ledertemperatur</b>         | Max. 70°C                                                  |
| <b>Kortslutningstemperatur</b> | Max. 160°C                                                 |
| <b>Håndteringstemperatur</b>   | Min. 10°C                                                  |
| <b>Lagertemperatur</b>         | Max. 40°C                                                  |

### Konstruksjon

|                      |                                      |
|----------------------|--------------------------------------|
| <b>Leder</b>         | Entrådet, glødd kobberleder          |
| <b>Isolasjon</b>     | Blyfri PVC                           |
| <b>Leder-merking</b> | Blå, brun                            |
| <b>Fyllkappe</b>     | Plast                                |
| <b>Jordleder</b>     | Blank kobberleder                    |
| <b>Metalkappe</b>    | Aluminiumsbånd (Limt til ytterkappe) |
| <b>Ytre kappe</b>    | Blyfri PVC                           |
| <b>Kapfefarge</b>    | Hvit                                 |

### Teknikk

|                      |                               |
|----------------------|-------------------------------|
| <b>Standard</b>      | NEK 535, IEC 60332-1/EN 50265 |
| <b>Driftspenning</b> | 300/500V                      |
| <b>Prøvespenning</b> | 2,5 kV AC                     |
| <b>CE-merket</b>     | LVD                           |

### N05VA5VH2-U

| Dimensjon       | Leder<br>Antall tråder og<br>diameter | Levering | Ytre<br>diameter<br>nom. | Ca. vekt  | EI- nr. | EAN- nr.                                                                              |
|-----------------|---------------------------------------|----------|--------------------------|-----------|---------|---------------------------------------------------------------------------------------|
| mm <sup>2</sup> | mm                                    | m        | mm                       | kg pr. km |         |                                                                                       |
| 2X1,5/1,5       | 1 x 1,36                              | B/50     | 5,8 x 8,2                | 90        | 1056200 |  |
| 2X1,5/1,5       | 1 x 1,36                              | T/500    | 5,8 x 8,2                | 90        | 1056210 |  |
| 2X2,5/2,5       | 1 x 1,76                              | B/50     | 6,8 x 9,5                | 124       | 1056203 |  |
| 2X2,5/2,5       | 1 x 1,76                              | T/450    | 6,8 x 9,5                | 124       | 1056213 |  |

### N05VA5V-U

| Dimensjon       | Leder<br>Antall tråder og<br>diameter | Levering | Ytre<br>diameter<br>nom. | Ca. vekt  | EI- nr. | EAN- nr.                                                                              |
|-----------------|---------------------------------------|----------|--------------------------|-----------|---------|---------------------------------------------------------------------------------------|
| mm <sup>2</sup> | mm                                    | m        | mm                       | kg pr. km |         |                                                                                       |
| 3X1,5/1,5       | 1 x 1,36                              | B/50     | 8,4                      | 134       | 1056201 |  |
| 3X1,5/1,5       | 1 x 1,36                              | T/350    | 8,4                      | 134       | 1056211 |  |

# Installasjonskabel

## PR, limt skjerm

### N05VA5V-U

| Dimensjon       | Leder<br>Antall tråder og<br>diameter | Levering | Ytre<br>diameter<br>nom. | Ca. vekt  | El- nr. | EAN- nr.                                                                                              |
|-----------------|---------------------------------------|----------|--------------------------|-----------|---------|-------------------------------------------------------------------------------------------------------|
| mm <sup>2</sup> | mm                                    | m        | mm                       | kg pr. km |         |                                                                                                       |
| 4X1,5/1,5       | 1 x 1,36                              | B/50     | 10,4                     | 157       | 1056202 |  7 071242 000106   |
| 4X1,5/1,5       | 1 x 1,36                              | T/250    | 10,4                     | 157       | 1056212 |  7 071242 000113   |
| 3X2,5/2,5       | 1 x 1,76                              | B/50     | 10,2                     | 196       | 1056204 |  7 071242 000182   |
| 3X2,5/2,5       | 1 x 1,76                              | T/250    | 10,2                     | 196       | 1056214 |  7 071242 000199   |
| 4X2,5/2,5       | 1 x 1,76                              | B/50     | 12,1                     | 226       | 1056205 |  7 071242 000229   |
| 4X2,5/2,5       | 1 x 1,76                              | T/200    | 12,1                     | 226       | 1056215 |  7 071242 000236   |
| 2X4/4           | 1 x 2,26                              | B/50     | 10,8                     | 228       | 1056206 |  7 071242 000267   |
| 2X4/4           | 1 x 2,26                              | T/250    | 10,8                     | 228       | 1056216 |  7 071242 000274  |
| 3X4/4           | 1 x 2,26                              | B/50     | 12,3                     | 272       | 1056207 |  7 071242 000304 |
| 3X4/4           | 1 x 2,26                              | T/200    | 12,3                     | 272       | 1056217 |  7 071242 000311 |