



Product description: Product code: Quantity:

64499 4008321393807 Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog: http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321393807

64499

Capabilities Dimmable Yes Burning position Any Country specific categorizations ILCOS HSGST/C/UB-205-230-B15D/98 Certificates & standards Certificates & standards EEI - Energy Label C Additional product data New article Disgn / version Auge: Standard designation) B15d NEW Corrs & materials
Country specific categorizations ILCOS HSGST/C/UB-205-230-B15D/98 Certificates & standards EEI - Energy Label C Additional product data Base (standard designation) B15d New article NEW Design / version Tube
Country specific categorizations ILCOS HSGST/C/UB-205-230-B15D/98 Certificates & standards EEI - Energy Label C Additional product data Base (standard designation) B15d New article NEW Design / version Tube
ILCOS HSGST/C/UB-205-230-B15D/98 Certificates & standards EEI - Energy Label C Additional product data Additional product data Base (standard designation) B15d New article NEW Design / version Tube Correct Coors & materials
Certificates & standards EEI - Energy Label C Additional product data Rase (standard designation) B15d New article NEW Design / version Tube
EEI - Energy Label C Additional product data Base (standard designation) B15d New article NEW Design / version Tube
EEI - Energy Label C Additional product data Base (standard designation) B15d New article NEW Design / version Tube
Additional product data Base (standard designation) New article Design / version Colors & materials
Base (standard designation) B15d New article NEW Design / version Tube Colors & materials
Base (standard designation) B15d New article NEW Design / version Tube Colors & materials
New article NEW Design / version Tube Colors & materials
Design / version Tube Colors & materials
Colors & materials
Rated lamp mercury content 0.0 mg
Mercury-free Yes
Electrical data
Rated wattage 205 W
Nominal wattage 205 W
Nominal voltage 230 V
Rated number of switching cycles 1000000 ¹⁾
Rated power factor λ 1.00
Dimensions & weight
Length 98.0 mm
Overall length 98.0 mm
Diameter 15.0 mm
Light center length (LCL) 67.0 mm
Outer bulb T15
Lifeenan
Lifespan Nominal lamp life time 2000 h
Rated lamp life time 2000 h
Light technical data
Nominal luminous flux 4200 lm
Rated luminous flux 4200 lm
Rated color temperature 3000 K
Rated color rendering index Ra 100
Rated starting time 0.0 s





Light technical data			
Rated warm-up time (60 %)	0 s		
Lumen main.fact.at end of nom.life time	0.80		

Packaging units					
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume	
4008321393807	Folding carton box contains 1 Piece	42,000 mm x 42,000 mm x 111,000 mm	36,000 g (0,000 g)	0,196 Cubic dec.	
4008321393814	Shipping carton box contains 12 Piece	140,000 mm x 127,000 mm x 180,000 mm	542,000 g (0,000 g)	3,200 Cubic dec.	

HALOLUX ECO: The compact package from OSRAM HALOLUX CERAM ECO is so slim it is perfect for narrow compact luminaires. It is available in wattages up to 205 W and can be operated without a transformer. It is characterized by its pure natural halogen light and is therefore the perfect high-performance lamp for modern sophisticated luminaires. • More compact dimensions than ordinary light bulbs • Available in a higher wattages up to 205 W • 100 % dimmable • The same pleasant quality of light as that of an incandescent lamp • Average life of 2,000 hours • No transformer required • UV filter

¹⁾ At 1 s on / 1 s off

