





CE EN 55015 • EN 61547 • EN 61347-2-13 • EN 60598-1 • EN 61000-3-2

EMC IP65 RoHS


KANSAS 80 8000 Lumen




KANSAS 50 5736 Lumen



KANSAS 30 3397 Lumen



KANSAS 10 750 Lumen



Type	Vare N°	Dimensjoner (mm)	Vekt kg	Lumen (lm)	°Kelvin	Inn Volt (V)	Watt W max	Strøm Faktor	Kartong dimensjoner (mm)
KANSAS 10	BFXTO110400N	130x110x50h	0,51	750	4000°	200÷240	10	>0,9	180x135x55h
KANSAS 30	BFXTO330400N	175x156x56h	1,00	3397	4000°	200÷240	30	>0,9	280x180x90h
KANSAS 50	BFXTO550400N	235x200x66h	1,93	5736	4000°	200÷240	50	>0,9	310x240x75h
KANSAS 80	BFXTO880400N	285x250x69h	2,90	8000	4000°	200÷240	80	>0,9	370x280x110h

LED Lyskaster Kansas

- Led lyskaster stillbar
- Driftspenning 200÷240V-AC 50÷60Hz
- IP65 Kapsling malt med sort epoxy
- Driftstemperatur -20°C ÷ +40°C°
- For profesjonell bruk
- CRI >80

LED flood

- Adjustable LED high power projector
- Power supply 200÷240V AC 50-60Hz
- IP65 enclosure painted with black epoxy
- Operating temperature -20°C ÷ +40°C°
- For professional use
- CRI >80

LED-PROJEKTOR

- Einstellbar High Brightness LED-Projektor
- Eingang: 200÷240VAC 50÷60Hz
- Schwarz Epoxy lackierte Gehäuse - IP65
- Betriebstemperatur: -20°C ÷ +40°C°
- Nur für berufliche Anwendung
- CRI >80

Projecteur LED

- Projecteur orientable Led à haute puissance
- Alimentation 200÷240V-AC 50÷60Hz
- Finition avec du vernis epoxy noir – IP65
- Température ambiante de fonctionnement -20°C ÷ +40°C°
- Usage professionnel
- CRI >80

Proyector LED

- Proyector LED ajustable de alta potencia
- Fuente de alimentación de 200÷240V AC 50-60Hz
- Caja IP65 pintada con epoxi negro
- Temperatura de funcionamiento -20°C ÷ +40°C°
- Para uso profesional
- CRI >80