

Herning Wall Sort Mini 580/620/1220/1300lm 3000/4000K Ra>80 Faseavsnitt

El-nummer: 3102131
 EAN: 7021986239607
 SG artikkelnr: 623960



Elektrisk

Watt: 8W/17W
 Spenning: 220-240V
 Frekvens (Hz): 50/60Hz
 Maks. armaturer per sikring: B10: 30, B16: 47, C10: 50, C16: 80

Lysteknikk

Type lyskilde: LED
 Effektiv lysstrøm (lm): 580/620/1220/1300lm
 Effekt: 73/78/72/76lm/W
 Fargetemperatur: 3000/4000K
 Fargegjengivelse (Ra/CRI): Ra>80
 MacAdams faktor: SDCM: 3
 Levetid: L80/B20>50.000
 Lysstråling: Direkte
 Optikk: Glass
 UGR: UGR<22/25
 Fotobiologisk sikkerhet: RG 1

Dimmetype

Type: Faseavsnitt

Beskyttelse

Isolasjonsklasse: Klasse II

Materialer og overflater

Material: Aluminium

Montering/Tilkobling



Montering: Vegg, Innendørs / Utendør
 Tilkobling: Hurtigklemme
 Vindprosjisert areal: 0,0275m²

Dimensjoner

Lengde (mm) L: 331
 Bredde (mm) W: 182
 Høyde (mm) H: 181
 Vekt (kg) brutto/netto: 2.262 / 1.74

Forpakning

Forpakkingsstørrelse (mm): 345 x 190 x 200



7 0 2 1 9 8 6 2 3 9 6 0 7