

H541814

Hjelpeblokk 1NO/3NC

## Artikkelnummer: LADN13

El-nummer: 4176520

EAN13-nummer: 3389110383928

Tilbehør til Tesys D kontaktorer og F kontaktorer

### Technical information

#### ► **Sertifikater og standarder**

Standarder

BS 4794  
EN 60947-5-1  
IEC 60947-5-1  
NF C 63-140  
VDE 0660

Produktsertifikater

CSA  
UL

#### ► **Kompatibilitet**

Produktkompatibilitet  
sikringsstørrelse

CR1F  
10 A gG IEC 60947-5-1

#### ► **Tilkoblinger**

tilkoblinger - terminaler

skrutilkobling 1 cable 1...2.5 mm<sup>2</sup> - cable stiffness: fleksibel - med cable end  
skrutilkobling 1 cable 1...2.5 mm<sup>2</sup> - cable stiffness: fleksibel - uten cable end  
skrutilkobling 1 cable 1...2.5 mm<sup>2</sup> - cable stiffness: helkjernet - med cable end  
skrutilkobling 1 cable 1...2.5 mm<sup>2</sup> - cable stiffness: helkjernet - uten cable end  
skrutilkobling 2 cable 1...2.5 mm<sup>2</sup> - cable stiffness: fleksibel - med cable end  
skrutilkobling 2 cable 1...2.5 mm<sup>2</sup> - cable stiffness: fleksibel - uten cable end  
skrutilkobling 2 cable 1...2.5 mm<sup>2</sup> - cable stiffness: helkjernet - med cable end  
skrutilkobling 2 cable 1...2.5 mm<sup>2</sup> - cable stiffness: helkjernet - uten cable end

#### ► **Elektrisk**

pole contact composition  
[Ui] rated insulation voltage

1 NO + 3 NC  
690 V - conforming to IEC 60947-5-1  
600 V - certifications CSA  
600 V - certifications UL

[Ue] merkespenning  
[Ith] conventional free air thermal current  
Irms rated making capacity

690 V AC 25...400 Hz  
10 A at ≤ 60 °C  
140 A at ≤ 690 V AC conforming to IEC 60947-5-1  
250 A at ≤ 690 V DC conforming to IEC 60947-5-1

permissible short-time rating

100 A at -5...60 °C 1 s  
120 A at -5...60 °C 500 ms  
140 A at -5...60 °C 100 ms

minimum brytestrøm  
minimum switching voltage  
Isolasjonsmotstand

5 mA  
17 V  
> 10 MOhm

#### ► **Miljø**

environmental characteristic  
IP-grad  
protective treatment  
ambient air temperature for operation  
ambient air temperature for storage  
operating altitude

normale omgivelser  
IP2x conforming to VDE 0106  
TH conforming to IEC 60068  
-5...60 °C °C  
-60...80 °C °C  
3000 m uten derating in temperature

#### ► **Praktisk**

Hjelpekontakt funksjon	momentan
non-overlap time	1.5 ms on de-energisation (no overlap between NC and NO contact)
overlap time	1.5 ms on energisation (no overlap between NC and NO contact)
▶ <b>Installasjon</b>	
monteringsområde	front
▶ <b>Ytelse</b>	
protection type	gG fuse <= 10 A rating according to operational current for Ue <= 690 V
mechanical durability	30 Mcycles cycles
▶ <b>Fysiske mål</b>	
Vekt	0.05 kg kg
▶ <b>Produktmerking</b>	
range	TeSys
Produkt eller komponent type	hjelpekontakt blokk

#### Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: [kundesenter@no.schneider-electric.com](mailto:kundesenter@no.schneider-electric.com)