

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

870480 - PLF-INB-UNI-24M

Aanwezigheidsdetector Universeel

/productimages/870480.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Presence detector
Sensor type	Passive infrared
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
Animal zone	No
Integrated	
Relay	
Networkable	No
Optimum mounting height (m)	2.5
(VA)	800
Max. reach frontally (m)	12
Diameter reach on floor (m)	24
Remote operation	Yes
Response value luminosity adjustable	Yes
Max. mounting height (m)	2.5
Material	Plastic
Material quality	Thermoplastic
Colour	White
RAL-number (similar)	9010
Degree of protection (IP)	IP54
Min. switch-on time (s)	30
Max. duty cycle (min)	30
Yes	
(mm)	43.5
Response value luminosity (lx)	10 - 2000
Max. switching power (W)	2300
(W)	0.5
Built-in size (mm)	68
Temperature (°C)	-20 - +45
Number of switching zones	1
Frequency (Hz)	50 - 60
Scan angle (°)	360
Max. presence range (m ²)	465
Suitable for ceiling mounting	Yes
Anti-bacterial treatment	No
Width (mm)	105
Height (mm)	79
Diameter (mm)	105
Built-in depth (mm)	44.5
Built-in diameter (mm)	68
Yes	
(V)	220 - 240
Yes	



(m)	24
(m ²)	465
(st)	6
10 - 2000	
Yes	
Suitable for wall mounting	No