

# PUSH-BUTTON CONTROL

# CORDSET DIMMER


## CON COMANDO A PULSANTE







## VARIABLE PASSANTE DA FILO

### RH SNELLO

Della dimensione di un normale interruttore sez-zafilo, è un variatore elettronico da tavolo in classe II per lampade ad incandescenza ed alogene.  
*Same dimensions of a normal switch, is a dimmer for Incandescent or halogen lamps. Class II elec-tronic table dimmer.*

#### Trailing edge technology



 W min. max.	 V	 Hz	 LPH mm		
20÷160	220-240	50	22x83x22	•	20



RH SNELLO N  
cod. RL7150



RH SNELLO B  
cod. RL7155



RH SNELLO P  
cod. RL7160



RH SNELLO T  
cod. RL7165

### CABLATI - WIRED



RH SNELLO C-N  
cod. RL7150/E1



RH SNELLO C-B  
cod. RL7155/E1



RH SNELLO C-P  
cod. RL7160/E1



RH SNELLO C-T  
cod. RL7165/E1

# CORDSET LED DIMMER

PUSH-BUTTON CONTROL

VARIABLE LED PASSANTE DA FILO

CON COMANDO A PULSANTE

## RH SNELLO LED

Varialuce in Classe II

Class II electronic table dimmer.

Trailing edge technology



Compatibile con Lampadine LED dimmerabili delle migliori marche in commercio.

Compatible with dimmable LED bulbs from major producers.



4÷100\*  
max 10 lampadine LED / LED lamps

220-240

50

22x83x22

•

20

40÷160  
HALO LAMP

220-240

50

22x83x22

•

20



RH SNELLO LED N  
cod. RL7150/LED



RH SNELLO LED B  
cod. RL7155/LED



RH SNELLO LED P  
cod. RL7160/LED



RH SNELLO LED T  
cod. RL7165/LED

## SLIDE CONTROL

CON COMANDO A CURSORE

## RONDÓ LED

Varialuce elettronico da tavolo o pavimento in classe II.

Electronic floor class II dimmer

Trailing edge technology



Compatibile con Lampadine LED dimmerabili delle migliori marche in commercio.

Compatible with dimmable LED bulbs from major producers.

DIM	ON-OFF
4÷100W (LED)	0÷500W
40÷250W (HALO)	0÷500W

Selezione tramite Jumper per funzionamento una o due fonti luminose.  
Selectable via Jumper for operating one or two light sources.



4÷100\*  
max 10 lampadine LED / LED lamps

220-240

50

Ø 94x37

•

20

40÷250  
HALO lamps

220-240

50

Ø 94x37

•

20



RONDÓ N LED  
cod. RS5600/led (50pz)  
cod. RL5600/led (10 pz)



RONDÓ P LED  
cod. RQ1205/led



RONDÓ B LED  
cod. RS5618/led



RONDÓ T LED  
cod. RS5640/led

\*10 lampadine max è il numero garantito e verificato da L.C. RELCO, non esiste uno standard costruttivo per le lampade a LED quindi il dispositivo potrebbe funzionare correttamente anche con un numero maggiore, 15÷20, previa verifica ufficio tecnico L.C. RELCO.

\*10 bulbs is the maximum quantity tested and granted by LC RELCO. Currently a proper standard for led bulbs is missing, so we just can come to the conclusion that the device could work even with more bulbs, like 15 to 20, but we recommend not to proceed with this solution before LC RELCO has duly tested it in its laboratories.



Consiglia:  
Nuove lampade a LED Dimmerabili: Ambiente e Lumina

