



product details

64695ECO SST 120W 240V R7S 10XB11 OSRAM

Product description: 64695ECO SST 120W 240V R7S 10XB11 OSRAM ¹⁾
 Product code: 4008321325372
 Quantity: Blister (BLI) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=NO&it_p=4008321325372

Capabilities	
Dimmable	Yes
Country specific categorizations	
ILCOS	HDG-120-230-R7s-74,9
Certificates & standards	
EEI - Energy Label	C
Additional product data	
Base (standard designation)	R7s
New article	NEW
Design / version	Tube
Colors & materials	
Rated lamp mercury content	0.0 mg
Mercury-free	Yes
Electrical data	
Rated wattage	120 W
Nominal wattage	120 W
Nominal voltage	240 V
Claimed equivalent incand. lamp power	150 W
Rated number of switching cycles	1000000 ²⁾
Rated power factor λ	1.00
Dimensions & weight	
Length	74.9 mm
Overall length	80.3 mm
Diameter	12.0 mm
Outer bulb	T12
Lifespan	
Nominal lamp life time	1000 h
Rated lamp life time	1000 h
Light technical data	
Nominal luminous flux	2250 lm
Rated luminous flux	2250 lm
Rated color temperature	2950 K
Rated color rendering index Ra	100
Rated starting time	0.0 s
Rated warm-up time (60 %)	0 s



21.05.2012

Subject to change without notice. Errors and omission excepted.

© 2012 OSRAM AG

Page 1 of 2

**Light technical data**

Lumen main.fact.at end of nom.life time	0.80
---	------

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321325372	Blister contains 1 Piece	120,000 mm x 12,000 mm x 141,000 mm	20,500 g (0,000 g)	0,470 Cubic dec.
4008321325389	Shipping carton box contains 10 Piece	149,000 mm x 129,000 mm x 157,000 mm	287,000 g (0,000 g)	3,018 Cubic dec.

Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index R_a : 100
- Base: R7s

Product benefits

- Brilliant ECO accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO₂ emissions
- Lower thermal output (compared with the standard reference product)
- No transformer required

Areas of application

- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Ideal for emphasizing and accentuating the structure of a room

1) Fuse protection with indicated values recommended acc. to IEC60357, EN60357 | For outdoor applications and operation in damp locations special approved fixtures are required

2) At 1 s on / 1 s off