


## PFXP



### Application

PFXP is a PVC-insulated and PVC-sheathed house wiring cable for fixed installation on ladders, in walls, in conduits or ducts. For indoor and outdoor use, but not in ground or water. When installed outdoors, the cable shall be provided with an extra protection against direct sunlight. The insulation of the conductor shall be protected against UV light

### House wiring cable

Max conductor temperature: -25°C/+70°C  
 Voltage Rating  $U_0/U$ : 300/500V  
 CPR class: Eca

### Standards

Conductor: IEC 60228-2  
 Construction: SS 424 02 19-3  
 Flame retardant: EN50575:2014+A1:2016

### Construction

Conductor 1,5mm <sup>2</sup>	Bare stranded copper 7 X 0,52mm
Conductor 2,5mm <sup>2</sup>	Bare stranded copper 7 X 0,66mm
Insulation of conductors	PVC
Color/Marking (2 core)	blue, brown
Color/Marking (3 core)	yellow/green, blue, brown
Color/Marking (4 core)	yellow/green, blue, brown, black
Color/Marking (5 core)	yellow/green, blue, brown, black, grey
Bedding	Halogen free bedding compound
Outer sheath	PVC
Marking	ex. PFXP 3G1,5 300/500V AMO I CE

Type Code	Cross-section [mm <sup>2</sup> ]	Insulation thickness [mm]	Conductor diameter [mm]	Outer sheath thickness [mm]	Outer diameter [mm]
PFXP 2X1,5	1,5	0,7	3,0	1,2	10,0 ± 0,3
PFXP 3G1,5	1,5	0,7	3,0	1,2	10,0 ± 0,3
PFXP 4G1,5	1,5	0,7	3,0	1,2	10,5 ± 0,5
PFXP 5G1,5	1,5	0,7	3,0	1,2	11,6 ± 0,3
PFXP 2X2,5	2,5	0,8	3,6	1,2	11,5 ± 0,3
PFXP 3G2,5	2,5	0,8	3,6	1,2	11,5 ± 0,3
PFXP 4G2,5	2,5	0,8	3,6	1,2	11,6 ± 0,3
PFXP 5G2,5	2,5	0,8	3,6	1,2	12,6 ± 0,3

