



NB4LE Residual Current Operated Circuit Breaker (Electronic)

1. General

1.1 Function

Personnel and fire protection: Cable and line protection against overload and short-circuits.

1.2 Selection

Rated residual operating current

$I_{\Delta n} = 30\text{mA}$, additional protection in the case of direct contact.

RCD Type

Type A

RCD Type A is ensured for sinusoidal, alternating residual currents as well as for pulsed DC residual currents, whether they be quickly or slowly increase.

Tripping curve

B curve ($I_1=1.13I_n$; $I_2=1.45I_n$; $I_4=3I_n$; $I_5=5I_n$) protection and control of the circuits against overloads and short-circuits; protection for people and big length cables in TN and IT systems.

C curve ($I_1=1.13I_n$; $I_2=1.45I_n$; $I_4=5I_n$; $I_5=10I_n$) protection and control of the circuits against overloads and short-circuits; protection for resistive and inductive loads with low inrush current.

CK curve ($I_1=1.05I_n$; $I_2=1.3I_n$; $I_4=5I_n$; $I_5=10I_n$) protection and control of the circuit against overloads and short-circuits; protection for resistive and inductive loads with low inrush current.

1.3 Approvals and certificates

CE/CB


1.4 Add-on devices

XF9 auxiliary contacts

S9 shunt release

V9 under voltage release

Line out in top (utgående side)






Supply-side (tilførsel i bunn)

CE

CB

2. Technical data

2.1 Curves





2.2

	Standard		IEC/EN 61009-1	
Electrical features	Type (wave form of the earth leakage sensed)		A	
	Thermo-magnetic release characteristic		B, C	CK
	Rated current I _n	A	6, 10, 13, 16, 20, 25, 32	10, 13, 15, 20
	Poles		2P	
	Rated voltage U _e	V	230/240	
	Rated sensitivity I _{Δn}	A	0.03	
	Rated residual making and breaking capacity I _{Δm}	A	3,000	
	Rated short-circuit capacity I _{cn}	A	6,000	
	Break time under I _{Δn}	s	≤0.1	
	Rated frequency	Hz	50/60	
	Rated impulse withstand voltage (1.2/50)U _{imp}	kV	4	
	Dielectric TEST voltage at ind. Freq. for 1min	kV	2	
	Insulation voltage U _i	V	500	
	Pollution degree		2	
Mechanical features	Electrical life		2,000	
	Mechanical life		10,000	
	Contact position indicator		Yes	
	Protection degree		IP20	
	Ambient temperature (with daily average ≤35°C)	°C	-25...+40	
	Storage temperature	°C	-25...+70	
Installation	Terminal connection type		Cable/U-type busbar/Pin-type busbar	
	Terminal size top/bottom for cable	mm ²	25	
		AWG	18-3	
	Terminal size top/bottom for busbar	mm ²	10	
		AWG	18-8	
	Tightening torque	N·m	2	
		In-lbs.	18	
	Mounting		On DIN rail EN 60715 (35mm) by means of fast clip device	
	Connection		Bottom electrical feeding	

2.3 Temperature derating

The maximum permissible current in a circuit breaker depends on the ambient temperature where the circuit breaker is placed. Ambient temperature is the temperature inside the enclosure or switchboard in which the circuit breakers are installed.
The reference temperature is 30°C

Temperature	-10°C	0°C	10°C	20°C	30°C	40°C	50°C	60°C
Temperature compensation coefficient of rated current	1.20	1.15	1.10	1.05	1.00	0.95	0.90	0.85

3. Overall and mounting dimensions (mm)

