





Velia 10.9W, 2700K

Technical data

Voltage	220-240 VAC 50 Hz
System effect	10.9W
Light source	9W LED, item no. 31110002 
Colour temperature	2700 Kelvin
Light intensity	650 Lumen
Colour rendering	CRI>95
Expected lifespan	30,000 hours L70 B50
Dimmable	Yes, trailing edge
Flicker free	Yes, according to the new Ecodesign / ErP directive
SVM <0.4	Yes
PstLM <1	Yes
SDCM	<3
Beam angle	38°
Carving dimensions	Ø75 mm
Installation height	68 mm
Exterior dimensions	Ø82 mm
Dimensions driver	L: 95 mm, W: 45 mm, H: 30 mm
Dimensions connector box	L: 85 mm, W: 55 mm, H: 30 mm
Possibility of through wiring	Yes, 3G1.5
IP-class	IP44 (is intended for installation in areas 1 and 2)
Insulation class	Class II
Material	Plastic, aluminium, glass
Environment	Indoors
Warranty	5 years
Approvals	CE



*The drawing is not drawn to scale

Product information

- Approved for installation directly in insulation and flammable materials
- High colour rendering index (CRI)
- High lumen output
- Glare free
- Flicker free according to the new Ecodesign / ErP directive
- Mounting with springs
- Comes with removable driver, which makes it easy to connect the downlight, for example after painting of the ceiling
- Quick and easy mounting
- Screwless terminal block in the connector box
- Ceiling thickness for mounting is up to 26 mm

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.

Item no.	EAN no.	Colour	Front design
31111012	5704629000018	Matt white	Round
31111092	5704629000015	Matt black	Round