



| SPECIFICATION | | DATA | |
|-----------------------------|-----------------------|---------------------|-----------------|
| Material and thickness | Cold roll steel 0.8mm | System power | 20W |
| Diffuser Material | | Total Lumen | 4320LM |
| Reflector/purity | | System efficiency | 108LM/W |
| Cross plates Quantity V | 0 | UGR | <20 |
| Frame Material/color | Metal/White | Beam angle | 111.2 |
| Certificates | CE RoHS EN62471 | Driver brand | |
| Class | I | Dimmable | AVAILABLE |
| IP | IP40 | PF | >0.96% |
| Warranty | 5 YEARS | THD | <20% |
| IK | IK05(0.7J) | Flicker free | <10% |
| Glow wires | | LED Chip brand | Seoul |
| Connector | | LED PCB board | 2PCS |
| Cut out hole | | CRI | >80 |
| External size | | LM80 8000 hours | 97.9(55degrees) |
| Weight | 1.3KGS | L70/B50 hours | YES |
| Size | 600x210x90mm | IES file available | YES |
| Box Quantity packaging size | 63.5x46x26cm 6pcs | LM79 | YES |
| Quantity for 40"HighCube | 3000pcs | Low Color Tolerance | ANSI/MacAdam 3 |
| | | DC Voltage range | 54~150V |

MARS KJØKKENARMATUR 20W

 This luminaire contains built-in LED lamps.

 LED

The LED lamps cannot be changed in the luminaire

874/2012 