



product details

**DULUX D/E 18 W/830**

Product description: DULUX D/E 18 W/830  
Product code: 4050300327211  
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

[http://catalog.myosram.com?~language=EN&~country=COM&it\\_p=4050300327211](http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300327211)

Applications	
Suitable for indoor	Yes

Categorizations	
SEG number	8330188

Certificates & Standards	
EEL - Energy Label	B

General Description	
Rated lamp mercury content	2.6 mg
Base (standard designation)	G24q-2
Recycling	Yes

Technical - Electrical Data	
Construction wattage	N/A
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body
Rated lamp efficacy (standard condition)	67 lm/W
Nominal wattage	18 W
Nominal voltage	220 V

Technical - Geometries	
Overall length	146.00 mm
Diameter	12.00 mm
Tube diameter	12 mm
Length with base excl. base pins/connect	130 mm
Length	146.00 mm
Length acc. to IEC standard	140 mm
Construction length	146.00 mm

Technical - Lifespan	
Operation mode LLMF/LSF	50 Hz
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000 h	0.80
Rated lamp survival factor at 20,000 h	0.50

Technical - Light Technical Data	
Rated color rendering index Ra	>=80
Nominal luminous flux	1200 lm



06.12.2011

Subject to change without notice. Errors and omission excepted.

© 2011 OSRAM AG

Page 1 of 2



## product details

## DULUX D/E 18 W/830

Technical - Light Technical Data	
Luminous flux at 25 °C	1200 lm
Rated luminous flux	1200 lm
Luminous flux	1200 lm
Light color	830
Rated color temperature	3000 K
Color rendering index Ra	80...89
Light color as per EN 12464-1	LUMILUX Warm White
Rated LLMF at 2,000 h	0.90
Rated LLMF at 4,000 h	0.84
Rated LLMF at 6,000 h	0.82
Rated LLMF at 8,000 h	0.81
Rated LLMF at 12,000 h	0.78
Rated LLMF at 16,000 h	0.78
Rated LLMF at 20,000 h	0.76
Color rendering group	1B
Color temperature	3000 K

Technical - Temperatures	
Rated ambient temp.w.max.luminous flux	25.0 °C

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300327211	Folding carton box contains 1 Piece	36,000 mm x 36,000 mm x 161,000 mm	50,000 g (0,000 g)	0,209 Cubic dec.
4050300327228	Shipping carton box contains 10 Piece	135,000 mm x 174,000 mm x 133,000 mm	606,500 g (0,000 g)	2,621 Cubic dec.

These compact fluorescent lamps can be operated on battery, solar or ac power. They are suitable for high-voltage and low-voltage ranges. They can also be fully dimmed. Their dimensions and wattages are identical to those of the successful standard OSRAM DULUX D models. The fact that they can be used with separate electronic control gear means they can be connected to almost any type of power supply, including ac, batteries and solar cells. Major applications include dimming and battery-powered emergency lighting in department stores, office buildings and so on.

- Comfortable light in ECG operation
- Shortened base casing to prevent two-pin lamps being fitted in new D/E holders, but still still fits in old D/E holders