

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

## 870050 - WATCHER-150

**Bewegingsmelder opbouw**

Package type: CT á 1 st



**PRODUCT SPECIFICATIONS:**

Model	Movement sensor
Sensor type	Passive infrared
Type	Complete sensor
Technique	Passive infrared
Mounting method	Surface mounted (plaster)
Constant light control	No
Contact	Relay
HVAC-control	No
Forced switch off	No
LED lights (VA)	150
Max. highfrequency EVSA	2
Max. switching power (W)	1000
Resistive load in Watts (W)	1000
Optimum mounting height (m)	2.5
Max. transmission range sideways (m)	6
Max. transmission range frontally (m)	12
Remote operation	No
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
Material	Plastic
Length (mm)	119.5
Width (mm)	73.5
Height (mm)	87.5
Dimfunction	No
Power consumption (W)	0.5
Material quality	Thermoplastic
Surface protection	Varnished
Type of surface	Matt
Colour	White
RAL-number (akin)	9010
Degree of protection (IP)	IP55
Voltage type	AC
Nominal voltage (V)	230
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 180
Response value luminosity (lx)	5 - 10000
Lensmask included	Yes
Temperature (°C)	-20 - +50
Frequency (Hz)	50 - 60
Voltage range (V)	220 - 240
Zero passage controlled relay	No
Puls	Yes

## 870050 - WATCHER-150

---



Lux adjustable	10 - 10000
Suitable for wall mounting	Yes
Suitable for ceiling mounting	Yes

