

PN 750 V Plastisolert koblingsledning

H07V-R

Plastisolert koblingsledning med flertrådet, glødd kobberleder.

Beskrivelse

Til inntrekking i rør for skjult opplegg.




Standarder

Internasjonal EN 50265; HD 21.3;
IEC 60332-1

Norsk NEK-HD 21.3



Blyfri
Ja



Maks. tillatt ledertemperatur
70 °C



RoHS conform
Ja



Flammehemmende
Ja

PN 750 V Plastisolert koblingsledning

Egenskaper


Konstruksjonsegenskaper	
Ledertype	Flertrådet, rund
Ledermateriale	Glødd kobber
Isolasjon	Polyvinylklorid - PVC
Blyfri	Ja
Bruksegenskaper	
Lengde	100 m
Maks. tillatt ledertemperatur	70 °C
RoHS conform	Ja
Flammehemmende	Ja

Produktliste

☎=Make to order, 📦=Make to stock

Nexans ref.	El. nummer	Produktnavn	Lederdiameter (mm)	Nominell ytre diameter (mm)	Vekt (ca.) (kg/100m)	Forpakning
📦 10022627	1050230	PN 750V 1,5 Sort SN150	1,6	3,0	2,1	Snelle
📦 10022622	1050231	PN 750V 1,5 Grå SN150	1,6	3,0	2,1	Snelle
📦 10022653	1050234	PN 750V 1,5 Blå SN150	1,6	3,0	2,1	Snelle
📦 10022644	1050236	PN 750V 1,5 G/G SN150	1,6	3,0	2,1	Snelle
📦 10022638	1050239	PN 750V 1,5 Brun SN150	1,6	3,0	2,1	Snelle
📦 10022628	1050240	PN 750V 2,5 Sort SN100	2,0	3,6	3,3	Snelle
📦 10022623	1050241	PN 750V 2,5 Grå SN100	2,0	3,6	3,3	Snelle
📦 10022654	1050244	PN 750V 2,5 Blå SN100	2,0	3,6	3,3	Snelle
📦 10022645	1050246	PN 750V 2,5 G/G SN100	2,0	3,6	3,3	Snelle
📦 10022639	1050249	PN 750V 2,5 Brun SN100	2,0	3,6	3,3	Snelle
📦 10022631	1050270	PN 750V 10 Sort 100m	4,0	6,0	11,0	Bunt
☎ 10022626	1050271	PN 750V 10 Grå 100m	4,0	6,0	11,0	Bunt
☎ 10022657	1050274	PN 750V 10 Blå 100m	4,0	6,0	11,0	Bunt

























☎ = Make to order, 📦 = Make to stock




 Blyfri
Ja

 Maks. tillatt ledertemperatur
70 °C

 RoHS conform
Ja

 Flammehemmende
Ja


PN 750 V Plastisolert koblingsledning

Nexans ref.	El. nummer	Produktnavn	Lederdiameter (mm)	Nominell ytre diameter (mm)	Vekt (ca.) (kg/100m)	Forpakning
 10022648	1050276	PN 750V 10 G/G 100m	4,0	6,0	11,0	Bunt
 10022642	1050279	PN 750V 10 Brun 100m	4,0	6,0	11,0	Bunt
 10022632	1050280	PN 750V 16 Sort 100m	5,0	7,0	17,3	Bunt
 10022637	1050282	PN 750V 16 Gul/Rød 100m	5,0	7,0	17,3	Bunt
 10022658	1050284	PN 750V 16 Blå 100m	5,0	7,0	17,3	Bunt
 10022649	1050286	PN 750V 16 G/G 100m	5,0	7,0	17,3	Bunt
 10022643	1050289	PN 750V 16 Brun 100m	5,0	7,0	17,3	Bunt
 10022633	1050320	PN 750V 25 Sort 50m	6,3	8,7	26,1	Bunt
 10022650	1050326	PN 750V 25 G/G 50m	6,3	8,7	26,1	Bunt
 10022634	1050330	PN 750V 35 Sort 50m	7,4	9,8	35,0	Bunt
 10022651	1050336	PN 750V 35 G/G 50m	7,4	9,8	35,0	Bunt
 10022684	1050410	PN 750V 16 Sort TR	5,0	7,0	17,3	Trommel
 10022694	1050412	PN 750V 16 Gul/Rød TR	5,0	7,0	17,3	Trommel
 10022699	1050416	PN 750V 16 G/G TR	5,0	7,0	17,3	Trommel
 10022685	1050420	PN 750V 25 Sort TR	6,3	8,7	26,1	Trommel
 10022695	1050425	PN 750V 25 Gul/Rød	6,3	8,7	26,1	Trommel
 10022700	1050426	PN 750V 25 G/G TR	6,3	8,7	26,1	Trommel
 10022686	1050430	PN 750V 35 Sort TR	7,4	9,8	35,0	Trommel
 10022701	1050436	PN 750V 35 G/G TR	7,4	9,8	35,0	Trommel
 10022687	1050440	PN 750V 50 Sort TR	8,7	11,5	47,0	Trommel
 10022696	1050442	PN 750V 50 Gul/Rød	8,7	11,5	47,0	Trommel
 10022702	1050446	PN 750V 50 G/G TR	8,7	11,5	47,0	Trommel
 10022688	1050450	PN 750V 70 Sort TR	9,9	12,7	66,2	Trommel
 10022703	1050456	PN 750V 70 G/G TR	9,9	12,7	66,2	Trommel

 = Make to order,  = Make to stock



Blyfri
Ja



Maks. tillatt ledertemperatur
70 °C



RoHS conform
Ja



Flammehemmende
Ja