

CONNECTUS / Plastic

Max. 16A/3680 W



· Supply cable: 2.0 m H05VV-F 3G 1.50 mm², black

Art. no.	Version	Dimensions: (L x W x H)
CONNECTUS		
1 x rocker switch, orange		
330.100	· 4 socket outlets with earthing contact	· approx. 355 x 72 x 49 mm
330.101	· 6 socket outlets with earthing contact	· approx. 440 x 72 x 49 mm
330.102	· 9 socket outlets with earthing contact	· approx. 570 x 72 x 49 mm
330.103	· 12 socket outlets with earthing contact	· approx. 695 x 72 x 49 mm

CONNECTUS 6 x earthing contact		
1 x overvoltage protection, 1 x orange rocker switch		
330.104	· 6 socket outlets with earthing contact · Overvoltage protection · Optical function and fail indicator	· approx. 480 x 72 x 49 mm

CONNECTUS 6 x earthing contact		
1 x overvoltage protection + mains and frequency filters, 1 x orange rocker switch		
330.105	· 6 socket outlets with earthing contact · Overvoltage protection + mains and frequency filters · Optical function and fail indicator	· approx. 568 x 72 x 49 mm

CONNECTUS 1 + 4 x earthing contact		
Master & slave		
330.106	· 1 master + 4 slave socket outlets with earthing contact · With threshold value setting	· approx. 480 x 72 x 42 mm

CONNECTUS 1 + 4 x earthing contact		
Master & slave, with overvoltage protection + mains and frequency filters		
330.107	· 1 master + 4 slave socket outlets with earthing contact · With threshold value setting · Overvoltage protection + mains and frequency filters · Optical function and fail indicator	· approx. 610 x 72 x 49 mm



Socket outlets