

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

/productimages/870048.jpg

**Bewegingsmelder opbouw**

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Model	Movement sensor
Sensor type	Passive infrared
With DALI interface	No
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
Forced switch off	No
Relay	
Optimum mounting height (m)	2
Max. reach sideways (m)	6
(VA)	150
Max. reach frontally (m)	12
Diameter reach on floor (m)	12
(W)	150
Remote operation	No
2	
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	1000
Mounting method	Surface mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface protection	Other
Surface finishing	Matt
Colour	Black
RAL-number (similar)	9005
Degree of protection (IP)	IP55
Voltage type	AC
Min. switch-on time (s)	5
(mm)	119.5
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 180
Pivoting range sensor, horizontal (°)	0 - 90
Pivoting range sensor, vertical (°)	0 - 130
Response value luminosity (lx)	10 - 10000
No	
Max. switching power (W)	1000
(W)	0.5
Temperature (°C)	-20 - +50
Number of switching zones	1



Max. starting current (A)	78
Frequency (Hz)	50 - 60
With alarm function	No
Scan angle (°)	180
Max. presence range (m <sup>2</sup> )	300
Suitable for ceiling mounting	Yes
Connection type	Screwed terminal
Width (mm)	73.5
Height (mm)	87.5
Depth (mm)	119.5
Max. switching power LED (W)	150
Yes	
Nominal voltage (V)	220 - 240
Yes	
Yes	
(m)	20
(m <sup>2</sup> )	120
(m <sup>2</sup> )	300
Suitable for wall mounting	Yes
No	
With connection cable	No