

H406082

Trykknapphode opphøyet grønn

## Artikkelnummer: ZB4BL3

El-nummer: 4302660

EAN13-nummer: 3389110887792

### Technical information

#### Tilleggsinformasjon

sale per indivisible quantity 1

#### Sertifikater og standarder

Standarder EN/IEC 60947-1  
EN/IEC 60947-5-1  
EN/IEC 60947-5-4  
EN/IEC 60947-5-5  
JIS C 4520  
UL 508  
CSA C22.2 No 14

Produktsertifikater BV  
CSA  
DNV  
GL  
LROS (Lloyds register of shipping)  
RINA  
UL listet

#### Miljø

protective treatment TH  
ambient air temperature for storage -40...70 °C °C  
ambient air temperature for operation -25...70 °C °C  
class of protection against electric shock klasse I conforming to IEC 60536  
IP-grad IP66 conforming to IEC 60529  
NEMA beskyttelsesgrad NEMA 13  
NEMA 4X  
IK beskyttelsesklasse IK03 conforming to IEC 50102  
Vibrasjonsmotstand 5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6  
30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27  
50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27

#### Praktisk

Type arm/stempel fjærretur  
operator profile grønn projecting umerket  
electrical composition code C1 for <= 9 contacts using single blocks in front mounting  
C2 for <= 9 contacts using single and double blocks in front mounting  
C11 for <= 3 contacts using single blocks in front mounting  
C15 for 1 contacts using single blocks in front mounting

#### Ytelse

mechanical durability 5000000 cycles cycles

#### Fysiske mål

Bredde 29 mm mm

Høyde 29 mm mm

Dybde 33 mm mm

shape of signaling unit head Rund

#### Produktmerking

Produktspekter Harmony XB4

Produkt eller komponent type head for non-illuminated pushbutton

kallenavn på utstyr

ZB4

Kant materiale

forkrommet metall

Montasjediameter

22 mm mm

### Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: [kundesenter@no.schneider-electric.com](mailto:kundesenter@no.schneider-electric.com)