

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

870470 - PLF-IB-PIR-ECO

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 st



PRODUCT SPECIFICATIONS:

Model	Presence detector
Sensor type	Passive infrared
Type	Complete sensor
Technique	Passive infrared
Mounting method	Flush mounted (plaster)
Sensor connector	Integrated
HVAC-control	No
Forced switch off	No
LED lights (VA)	800
(W)	600
Max. highfrequency EVSA	25
Max. switching power (W)	2000
Optimum mounting height (m)	2.5
Max. mounting height (m)	5
Max. transmission range sideways (m)	3.5
Max. transmission range frontally (m)	3.5
Diameter detection range on floor (m)	7
Remote operation	No
With remote control	No
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
Material	Plastic
Height (mm)	67
No	
Built-in height (mm)	65
Built-in size (mm)	63
Outerdiameter sensor (mm)	80
Colour	White
RAL-number (akin)	9010
Degree of protection (IP)	IP20
Voltage type	AC
Nominal voltage (V)	230
Min. switch-on time (s)	30
Pre-assembled	Not pre-assembled
Max. duty cycle (min)	30
Detection angle horizontal (°)	5 - 360
Response value luminosity (lx)	10 - 2000
Animal zone	No
Bridging switch	No
Lensmask included	Yes
Temperature (°C)	-10 - +40
Max. starting current (A)	800
Substation input	No
Frequency (Hz)	50 - 60



Voltage range (V)

220 - 240



Contacts

1 make contact (NO)

