



product details

64491

Product description: 64491
Product code: 4008321393319
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321393319

Capabilities	
Dimmable	Yes
Burning position	Any
Country specific categorizations	
ILCOS	HSGST/C/UB-40-230-B15D/67
Certificates & standards	
EEI - Energy Label	C
Additional product data	
Base (standard designation)	B15d
New article	NEW
Design / version	Tube
Colors & materials	
Rated lamp mercury content	0.0 mg
Mercury-free	Yes
Electrical data	
Rated wattage	40 W
Nominal wattage	40 W
Nominal voltage	230 V
Rated number of switching cycles	1000000 ¹⁾
Rated power factor λ	1.00
Dimensions & weight	
Length	67.0 mm
Overall length	67.0 mm
Diameter	13.0 mm
Light center length (LCL)	39.0 mm
Outer bulb	T13
Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h
Light technical data	
Nominal luminous flux	590 lm
Rated luminous flux	590 lm
Rated color temperature	2700 K
Rated color rendering index Ra	100
Rated starting time	0.0 s



Light technical data	
Rated warm-up time (60 %)	0 s
Lumen main.fact.at end of nom.life time	0.80

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321393319	Folding carton box contains 1 Piece	42,000 mm x 42,000 mm x 111,000 mm	27,000 g (0,000 g)	0,196 Cubic dec.
4008321393326	Shipping carton box contains 12 Piece	140,000 mm x 127,000 mm x 180,000 mm	390,000 g (0,000 g)	3,200 Cubic dec.

HALOLUX ECO: The compact package from OSRAM

HALOLUX CERAM ECO is so slim it is perfect for narrow compact luminaires. It is available in wattages up to 205 W and can be operated without a transformer. It is characterized by its pure natural halogen light and is therefore the perfect high-performance lamp for modern sophisticated luminaires.

- More compact dimensions than ordinary light bulbs
- Available in a higher wattages up to 205 W
- 100 % dimmable
- The same pleasant quality of light as that of an incandescent lamp
- Average life of 2,000 hours
- No transformer required
- UV filter

¹⁾ At 1 s on / 1 s off