

H404668

Plastkropp no/nc mom.kont

## Artikkelnummer: ZCP21

El-nummer: 4350623

EAN13-nummer: 3389110180206

### Technical information

#### Kompatibilitet

Produktkompatibilitet

XCKP

Tilhørende hode

ZCE01

ZCE02

ZCE05

ZCE06

ZCE07

ZCE08

ZCE09

ZCE10

ZCE11

ZCE13

ZCE14

ZCE21

ZCE24

ZCE27

ZCE28

ZCE29

ZCE62

ZCE63

ZCE64

ZCE65

ZCE66

ZCE67

ZCEH0

ZCEH2

associated connection component

ZCPEF12

ZCPEG11

ZCPEG13

ZCPEN12

ZCPEP16

ZCPEP20

#### Tilkoblinger

Elektrisk tilkobling

screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm<sup>2</sup>

#### Elektrisk

antall poler

2

Kontakt angivelse

B300, AC-15 (U<sub>e</sub> = 240 V, I<sub>e</sub> = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A

R300, DC-13 (U<sub>e</sub> = 250 V, I<sub>e</sub> = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A

[U<sub>i</sub>] rated insulation voltage

500 V degree of pollution 3 conforming to IEC 60947-1

300 V conforming to UL 508

300 V conforming to CSA C22.2 No 14

[U<sub>imp</sub>] rated impulse withstand voltage

6 kV conforming to IEC 60664

6 kV conforming to IEC 60947-1

short circuit protection

10 A by gG cartridge sikring

#### Miljø

ambient air temperature for operation

-25...70 °C

|                                     |                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ambient air temperature for storage | -40...70 °C °C                                                                                                                                                                                                                                                                                                                                                                     |
| <b>► Praktisk</b>                   |                                                                                                                                                                                                                                                                                                                                                                                    |
| Design                              | compact                                                                                                                                                                                                                                                                                                                                                                            |
| contacts type and composition       | 1 NC + 1 NO                                                                                                                                                                                                                                                                                                                                                                        |
| Kontaktens isolasjonsform           | Zb                                                                                                                                                                                                                                                                                                                                                                                 |
| contacts operation                  | momentan                                                                                                                                                                                                                                                                                                                                                                           |
| Positiv åpning                      | med                                                                                                                                                                                                                                                                                                                                                                                |
| Minimum aktiverings hastighet       | 0.01 m/s m/s                                                                                                                                                                                                                                                                                                                                                                       |
| <b>► Ytelse</b>                     |                                                                                                                                                                                                                                                                                                                                                                                    |
| Elektrisk levetid                   | 5000000 cycles, DC-13 120 V, 4 W, operating rate: < 60 cyc/mn,<br>load factor: 0,5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 24 V, 10 W, operating rate: < 60 cyc/mn,<br>load factor: 0,5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 7 W, operating rate: < 60 cyc/mn,<br>load factor: 0,5 conforming to IEC 60947-5-1 appendix C |
| <b>► Fysiske mål</b>                |                                                                                                                                                                                                                                                                                                                                                                                    |
| Materiale kropp                     | plast                                                                                                                                                                                                                                                                                                                                                                              |
| contacts material                   | silver plated contacts                                                                                                                                                                                                                                                                                                                                                             |
| Bredde                              | 31 mm mm                                                                                                                                                                                                                                                                                                                                                                           |
| Høyde                               | 65 mm mm                                                                                                                                                                                                                                                                                                                                                                           |
| Dybde                               | 30 mm mm                                                                                                                                                                                                                                                                                                                                                                           |
| Vekt                                | 0.07 kg kg                                                                                                                                                                                                                                                                                                                                                                         |
| <b>► Produktmerking</b>             |                                                                                                                                                                                                                                                                                                                                                                                    |
| Produktspekter                      | OsiSense XC                                                                                                                                                                                                                                                                                                                                                                        |
| Serie navn                          | Standard compact                                                                                                                                                                                                                                                                                                                                                                   |
| Produkt eller komponent type        | limit switch body                                                                                                                                                                                                                                                                                                                                                                  |
| kallenavn på utstyr                 | ZCP                                                                                                                                                                                                                                                                                                                                                                                |
| type kropp                          | fast                                                                                                                                                                                                                                                                                                                                                                               |

#### Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: [kundesenter@no.schneider-electric.com](mailto:kundesenter@no.schneider-electric.com)