





CE EN 55015 • EN 61547 • EN 61347-2-13 • EN 60598-1 • EN 61000-3-2

EMC IP65 RoHS


## KANSAS 80 8000 Lumen




## KANSAS 50 5736 Lumen



## KANSAS 30 3397 Lumen



## KANSAS 10 750 Lumen



| Type      | Vare N°      | Dimensjoner (mm) | Vekt kg | Lumen (lm) | °Kelvin | Inn Volt (V) | Watt W max | Strøm Faktor | Kartong dimensjoner (mm) |
|-----------|--------------|------------------|---------|------------|---------|--------------|------------|--------------|--------------------------|
| KANSAS 10 | BFXTO110400N | 130x110x50h      | 0,51    | 750        | 4000°   | 200÷240      | 10         | >0,9         | 180x135x55h              |
| KANSAS 30 | BFXTO330400N | 175x156x56h      | 1,00    | 3397       | 4000°   | 200÷240      | 30         | >0,9         | 280x180x90h              |
| KANSAS 50 | BFXTO550400N | 235x200x66h      | 1,93    | 5736       | 4000°   | 200÷240      | 50         | >0,9         | 310x240x75h              |
| KANSAS 80 | BFXTO880400N | 285x250x69h      | 2,90    | 8000       | 4000°   | 200÷240      | 80         | >0,9         | 370x280x110h             |

### LED Lyskaster Kansas

- Led lyskaster stillbar
- Driftspenning 200÷240V-AC 50÷60Hz
- IP65 Kapsling malt med sort epoxy
- Driftstemperatur -20°C ÷ +40°C°
- For profesjonell bruk
- CRI >80

### LED flood

- Adjustable LED high power projector
- Power supply 200÷240V AC 50-60Hz
- IP65 enclosure painted with black epoxy
- Operating temperature -20°C ÷ +40°C°
- For professional use
- CRI >80

### LED-PROJEKTOR

- Einstellbar High Brightness LED-Projektor
- Eingang: 200÷240VAC 50÷60Hz
- Schwarz Epoxy lackierte Gehäuse - IP65
- Betriebstemperatur: -20°C ÷ +40°C°
- Nur für berufliche Anwendung
- CRI >80

### Projecteur LED

- Projecteur orientable Led à haute puissance
- Alimentation 200÷240V-AC 50÷60Hz
- Finition avec du vernis epoxy noir – IP65
- Température ambiante de fonctionnement -20°C ÷ +40°C°
- Usage professionnel
- CRI >80

### Proyector LED

- Proyector LED ajustable de alta potencia
- Fuente de alimentación de 200÷240V AC 50-60Hz
- Caja IP65 pintada con epoxi negro
- Temperatura de funcionamiento -20°C ÷ +40°C°
- Para uso profesional
- CRI >80