

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko[®]

TECHNIEK BV

870540 - IB-PIR-WAND

Bewegingsmelder Inbouw

Package type: CT á 1 Pieces



PRODUCT SPECIFICATIONS:

Model	Movement sensor
Type	Complete sensor
Technique	Passive infrared
Mounting method	Flush mounted (plaster)
Voltage range (V)	220 - 240
Nominal voltage (V)	230
Voltage type	AC
Contacts	1 make contact (NO)
Resistive load in Watts (W)	1600
Max. highfrequency EVSA	2
LED lights (VA)	500
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Degree of protection (IP)	IP40
Power consumption (W)	0.6
Optimum mounting height (m)	1
Detection angle horizontal (°)	1 - 180
Diameter detection range on floor (m)	8
Max. switching power (W)	1600
Remote operation	No
Response value sensitivity adjustable	Yes
Response value luminosity (lx)	5 - 10000
Response value luminosity adjustable	Yes
Temperature (°C)	-10 - +45
Material	Plastic
Constant light control	No
HVAC-control	No
Lux adjustable	5 - 10000
Contact	Relay
Forced switch off	Yes
Max. transmission range sideways (m)	8
Max. transmission range frontally (m)	8
Material quality	Thermoplastic
Type of surface	Brilliant
Colour	White
RAL-number (akin)	9010
Frequency (Hz)	50 - 60
Selflearning luxvalue	Yes
Lensmask included	Yes
Suitable for wall mounting	Yes
Suitable for ceiling mounting	No
Length (mm)	80
Width (mm)	80
Height (mm)	56

870540 - IB-PIR-WAND

