



Description

Multifix Multi boxes are mainly intended for renovation work. They are perfect when flush-mounted devices need to be added to your existing installations in studwork walls.

The range includes a single, a 1.5 module and a double box, all adapted to a c/c distance of 60 mm. The single box can be used in single or double boards, whereas the 1.5 module and double boxes are suitable for single or double/triple boards.

The single box has two screws to fix the box to the wall board and two to secure the outlet. In the 1.5 module and double boxes the screws have a combi-function for these two purposes.

Standards & approvals

Standards	IEC 695-2-1, Glow wire test
	IEC 60670-1
	NEMKO NEK 516:82
	FIMKO EMKO TUI (23B) FI 241/92-01 and SFS 3717:1981
Approvals	SEMKO, NEMKO, FIMKO.

Patents & certificates

Patents	Material: Flame retardant polymer composition (Altair), EP1198499 (A1)
---------	------------------------------------------------------------------------

Material data

PE-HD (Altair: polyethylene, high density)	Density	1.36 g/cm ³
	Flammability prop.	Passed glow wire test, 850°C
	Colour spec.	Schneider grey 1
PA6 (polyamide), 30% glass-fibre	Density	1.35 g/cm ³
	Colour	Natural

Operative data

Temperature range	Operating temperature from -25°C to +90°C
Suitable outdoors	Not suitable

Mounting instruction

Mounting instruction are enclosed with the products. They are also available on PI@net.

Art.No. 0075313 / 20058460	Multi box, double
Art.No. 0075298 / 20056523	Apparatus box, 1.5 module

Product Environmental Facts


Product Environmental Fact files are available on PI@net.


Package info

Package information is included in the Prodat file, which is available in the SAP system. Package information can also be obtained from the responsible factory.


Multifix Multi

P113124




Type	Colour	Dimensions A/B/C (mm)		Qty per package	EAN code	Internal ID-No.	Target market	Ref. No.
Apparatus box, single								
Single Multi apparatus box, 60 mm high, to be used for additional installations of devices with a c/c 60 mm distance, in studwork walls of single or double plasterboard. Four angled entries for Ø16 mm flexible conduit at the bottom, two to each side. Material: PE-HD.								
Multi box, single	Grey	82/62/82		50	3606485113357	20059876	SE, NO	IMT36056
Single Multi apparatus box like the above for the do-it-yourself market. Material: PE-HD.								
Multi box, single, DIY	Grey	82/62/82		10	3606480165153	20061531	SE	IMT36331

P113101




Apparatus box, 1.5 module								
Multi apparatus box, 1.5 module, with integrated fixings for board thicknesses 6–39 mm. Interface for stub/strain relief. Knock-outs for flexible conduits Ø16 and Ø20 mm. Drill template included. Material: PE-HD.								
Multi box, 1.5 module	Grey	98/58/85		50	3606485112077	20059506	SE, NO, FI	IMT36026

P113104




Apparatus box, double								
Double Multi apparatus box with integrated fixings for board thicknesses 6–26 mm. Interface for stub/strain relief. Knock-outs for flexible conduits Ø16 and Ø20 mm. Material: PE-HD.								
Multi box, double	Grey	143/78/57		25	3606485112114	20059510	SE, NO, FI	IMT36030

P116348



Strain relief devices								
Strain relief with screw for cable 9–13 mm. Intended for the single box. Material: PA6.								
Strain relief 9–13 mm	Natural	Ø23/14		50	3606485133881	20060117	SE, NO	IMT36067

P116387



Strain relief for F/K cable. Intended for the single box. Material: PA6.								
Strain relief F/K	Natural	28/15/14		50	3606485133874	20060115	SE, NO	IMT36066