

## 19" IT PDU Protection (230 V / 50 Hz)

For description, see page 177



| Art. no. | Version | Colour (plastic / profile) |
|----------|---------|----------------------------|
|----------|---------|----------------------------|

**19" IT PDU Basic with fusing**

10 A miniature fuse, 2.0 m H05VV-F 3G 1.00 mm², black, with IEC320 C14 plug

333.410 8 socket outlets with earthing contact, red light grey / silver

333.538 8 socket outlets with earthing contact, red black / black

10 A miniature fuse, 2.0 m H05VV-F 3G 1.50 mm², black, with right angle plug with earthing contact

333.408 8 IEC320 non-heating appliance socket outlets C13 black light grey / silver

10 A miniature fuse, 2.0 m H05VV-F 3G 1.00 mm², black, with IEC320 C14 plug

333.540 8 IEC320 non-heating appliance socket outlets C13 black light grey / silver

1 x residual current device, 16 A, tripping current 30 mA

333.411 6 socket outlets with earthing contact, light grey light grey / silver

1 x MCB 16 A type B

333.412 6 socket outlets with earthing contact, light grey light grey / silver

## Zero U-Space IT PDU Basic (230 V / 50 Hz)



| Art. no. | Version | Colour (plastic / profile) |
|----------|---------|----------------------------|
|----------|---------|----------------------------|

**Zero U-Space IT PDU Basic**

Without switch, 2.0 m H05VV-F 3G 1.50 mm², black, with right angle plug with earthing contact

333.413 12 socket outlets with earthing contact, light grey light grey / silver

## 10" IT PDU Basic (230 V / 50 Hz)



| Art. no. | Version | Colour (plastic / profile) |
|----------|---------|----------------------------|
|----------|---------|----------------------------|

**IT PDU Basic**

10 ", 2.0 m H05VV-F 3G 1.50 mm², black, with right angle plug with earthing contact

333.417 3 socket outlets with earthing contact, light grey light grey / silver

333.0122 4 socket outlets with earthing contact, light grey light grey / silver