

Installasjonskabel

PR, limt skjerm



Bruksområde

Bruksområde	Husinstallasjonskabel til fast opplegg innen- og utendørs.
Ledertemperatur	Max. 70°C
Kortslutningstemperatur	Max. 160°C
Håndteringstemperatur	Min. 10°C
Lagertemperatur	Max. 40°C

Konstruksjon

Leder	Entrådet, glødd kobberleder
Isolasjon	Blyfri PVC
Leder-merking	Blå, brun
Fyllkappe	Plast
Jordleder	Blank kobberleder
Metalkappe	Aluminiumsbånd (Limt til ytterkappe)
Ytre kappe	Blyfri PVC
Kapfefarge	Hvit

Teknikk

Standard	NEK 535, IEC 60332-1/EN 50265
Driftspenning	300/500V
Prøvespenning	2,5 kV AC
CE-merket	LVD

N05VA5VH2-U

Dimensjon	Leder Antall tråder og diameter	Levering	Ytre diameter nom.	Ca. vekt	EI- nr.	EAN- nr.
mm ²	mm	m	mm	kg pr. km		
2X1,5/1,5	1 x 1,36	B/50	5,8 x 8,2	90	1056200	
2X1,5/1,5	1 x 1,36	T/500	5,8 x 8,2	90	1056210	
2X2,5/2,5	1 x 1,76	B/50	6,8 x 9,5	124	1056203	
2X2,5/2,5	1 x 1,76	T/450	6,8 x 9,5	124	1056213	

N05VA5V-U

Dimensjon	Leder Antall tråder og diameter	Levering	Ytre diameter nom.	Ca. vekt	EI- nr.	EAN- nr.
mm ²	mm	m	mm	kg pr. km		
3X1,5/1,5	1 x 1,36	B/50	8,4	134	1056201	
3X1,5/1,5	1 x 1,36	T/350	8,4	134	1056211	

Installasjonskabel

PR, limt skjerm

N05VA5V-U

Dimensjon	Leder Antall tråder og diameter	Levering	Ytre diameter nom.	Ca. vekt	El- nr.	EAN- nr.
mm ²	mm	m	mm	kg pr. km		
4X1,5/1,5	1 x 1,36	B/50	10,4	157	1056202	 7 071242 000106
4X1,5/1,5	1 x 1,36	T/250	10,4	157	1056212	 7 071242 000113
3X2,5/2,5	1 x 1,76	B/50	10,2	196	1056204	 7 071242 000182
3X2,5/2,5	1 x 1,76	T/250	10,2	196	1056214	 7 071242 000199
4X2,5/2,5	1 x 1,76	B/50	12,1	226	1056205	 7 071242 000229
4X2,5/2,5	1 x 1,76	T/200	12,1	226	1056215	 7 071242 000236
2X4/4	1 x 2,26	B/50	10,8	228	1056206	 7 071242 000267
2X4/4	1 x 2,26	T/250	10,8	228	1056216	 7 071242 000274
3X4/4	1 x 2,26	B/50	12,3	272	1056207	 7 071242 000304
3X4/4	1 x 2,26	T/200	12,3	272	1056217	 7 071242 000311