

L 58 W/965

LUMILUX DE LUXE T8 | Tubular fluorescent lamps 26 mm, with G13 bases



- Ideal where color rendering is an important factor
- Public buildings
- Shops
- Supermarkets and department stores
- Industry

Product benefits

- Excellent color rendering
- Natural colors
- Available in many different light colors (3,000...6,500 K) for every application and preference
- High luminous flux

Product features

- Very good color rendering group: 1A ($R_a: \geq 90$)
- Long service life: up to 16,000 h (with preheat ECG)
- Dimmable



Technical data

Electrical data


Nominal wattage	58 W
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body
Rated lamp efficacy (standard condition)	78 lm/W
Rated wattage	58 W

Light technical data

Color rendering index Ra	>=90
Rated luminous flux	4550 lm
Luminous flux at 25 °C	4550 lm
Light color	965
Color temperature	6500 K
Nominal luminous flux	4550 lm
Light color as per EN 12464-1	LUMILUX DE LUXE Cool Daylight
Rated LLMF at 2,000 h	0.92
Rated LLMF at 4,000 h	0.90
Rated LLMF at 6,000 h	0.88
Rated LLMF at 8,000 h	0.86
Rated LLMF at 12,000 h	0.85
Color coordinates chromaticity diagram	0.313/0.327

Dimensions & weight

Tube diameter	26 mm
Length	1500.0 mm
Length with base excl. base pins/connection	1500.00 mm
Diameter	26.0 mm



G13
IEC 7004-51
DIN 49653 T1

Product line drawing with letters

Base

Colors & materials

Lamp mercury content	4.6 mg
----------------------	--------

Temperatures

Rated ambient temp.w.max.luminous flux	25.0 °C
--	---------


Lifespan

Service life	16000 h ¹⁾
Lifespan	20000 h ¹⁾
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.90
Operation mode LLMF/LSF	50 Hz

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	G13
Appropriate disposal acc. to WEEE	Yes



Spectral power distribution

Capabilities

Suitable for indoor	Yes
---------------------	-----

Certificates & standards

EEI – Energy Label	B
--------------------	---

Lamp-ECG combination (System)

HF 1x58/230-240 DIM

Nominal current	0.25 (A)
Nominal wattage	56 (W)
Nominal wattage + Power loss	2.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	0...+50 (°C)
Number of lighting outlets	1

Products

HF 1x58/230-240 DIM

HF 2x58/230-240 DIM

Nominal current	0.48 (A)
Nominal wattage	111 (W)
Nominal wattage + Power loss	5.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	0...+50 (°C)
Number of lighting outlets	2

Products

HF 2x58/230-240 DIM

QT-FIT8 1x58-70

Nominal current	0.24 (A)
Nominal wattage	49 (W)
Nominal wattage + Power loss	5.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-15...+50 (°C)
Number of lighting outlets	1

Products

QT-FIT8 1x58-70

QT-FIT8 2x58-70

Nominal current	0.48 (A)
Nominal wattage	99 (W)
Nominal wattage + Power loss	10.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-15...+50 (°C)
Number of lighting outlets	2

Products

QT-FIT8 2x58-70

QTP5 1x54

Nominal current	0.25 (A)
Nominal wattage	50 (W)
Nominal wattage + Power loss	5.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-20...+50 (°C)
Number of lighting outlets	1

Products

QTP5 1x54

QTP5 2x54

Nominal current	0.48 (A)
Nominal wattage	100 (W)
Nominal wattage + Power loss	9.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-20...+50 (°C)
Number of lighting outlets	2

Products

QTP5 2x54

QTP8 1x58

Nominal current	0.24 (A)
Nominal wattage	50 (W)
Nominal wattage + Power loss	5.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-25...+55 (°C)
Number of lighting outlets	1

Products

QTP8 1x58/230-240

QTP8 2x58

Nominal current	0.45 (A)
Nominal wattage	100 (W)
Nominal wattage + Power loss	10.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-25...+55 (°C)
Number of lighting outlets	2

Products

QTP8 2x58/230-240

QTi 1x28/54/35/49 GII

Nominal current	0.24 (A)
Nominal wattage	50 (W)
Nominal wattage + Power loss	5.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-20...+50 (°C)
Number of lighting outlets	1

Products

QTi 1x28/54/35/49 GII

QTi 1x58 DIM

Nominal current	0.25 (A)
Nominal wattage	50 (W)
Nominal wattage + Power loss	6.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-20...+50 (°C)
Number of lighting outlets	1

Products

QTi 1x58 DIM

QTi 2x28/54/35/49 GII

Nominal current	0.47 (A)
Nominal wattage	98 (W)
Nominal wattage + Power loss	11.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-20...+50 (°C)
Number of lighting outlets	2

Products

QTi 2x28/54/35/49 GII

QTi 2x58 DIM

Nominal current	0.47 (A)
Nominal wattage	100 (W)
Nominal wattage + Power loss	8.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-20...+50 (°C)
Number of lighting outlets	2

Products

QTi 2x58 DIM

QTi DALI 1x58 DIM

Nominal current	0.25 (A)
Nominal wattage	50 (W)
Nominal wattage + Power loss	6.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	+10...+50 (°C)
Number of lighting outlets	1

Products

QTi DALI 1x58 DIM

QTi DALI 2x58 DIM


Nominal current	0.47 (A)
Nominal wattage	100 (W)
Nominal wattage + Power loss	8.00 (W)
Luminous flux	5000 (lm)
Ambient temperature range	-20...+50 (°C)
Number of lighting outlets	2

Products

QTi DALI 2x58 DIM

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp



Circuit diagram

Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4008321090034	Sleeves 1	27 mm x 27 mm x 1515 mm	232.00 g	1.10 dm ³
4008321090041	Shipping carton box 25	147 mm x 845 mm x 853 mm	6679.00 g	105.96 dm ³

References / Links

For more information on QUICKTRONIC electronic control gear go to

▶ www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.