



## Main

Range	Merten
Product name	System Design
Product or component type	Socket-outlet
Device presentation	Mechanism with fixing frame and cover plate

## Complementary




Device mounting	Flush
Fixing mode	By screws and claws
Device application	Power supply
Socket number	1
Outlet poles configuration	2P + E
Outlet standard	Schuko
Outlet standard	CEE 7/3
Cover type	With shutter
Rated current	16 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Colour tint	Anthracite (RAL 7024)
Material	Thermoplastic
Surface treatment	Varnished
Surface finish	Matt
Connections - terminals	Screwless terminals
IP degree of protection	IP20
Width	71 mm
Height	71 mm
Depth	40 mm
Standards	DIN 49440

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	7.3 cm
Package 1 Length	7.3 cm
Package 1 Weight	84.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	8.9 cm

Package 2 Width	17.9 cm
Package 2 Length	26.8 cm
Package 2 Weight	967.0 g
Unit Type of Package 3	CAR
Number of Units in Package 3	40
Package 3 Height	18.5 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	4.27 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>