



product details

66733 ECO

Product description: 66733 ECO
Product code: 4008321226341
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321226341

Capabilities	
Dimmable	Yes
Burning position	Any
Country specific categorizations	
ILCOS	HSGST/C/UB-33-240-G9-22
Certificates & standards	
EEI - Energy Label	C
Additional product data	
Base (standard designation)	G9
Design / version	Tube
Colors & materials	
Rated lamp mercury content	0.0 mg
Mercury-free	Yes
Electrical data	
Rated wattage	33 W
Nominal wattage	33 W
Nominal voltage	240 V
Rated number of switching cycles	1000000 ¹⁾
Rated power factor λ	1.00
Dimensions & weight	
Length	43.0 mm
Overall length	43.0 mm
Diameter	14.0 mm
Light center length (LCL)	22.0 mm
Outer bulb	T13,3
Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h
Light technical data	
Nominal luminous flux	460 lm
Rated luminous flux	460 lm
Rated color temperature	2700 K
Rated color rendering index Ra	100
Rated starting time	0.0 s
Rated warm-up time (60 %)	0 s

**Light technical data**

Lumen main.fact.at end of nom.life time	0.80
---	------

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321226341	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	6,500 g (0,000 g)	0,045 Cubic dec.
4008321226358	Shipping carton box contains 20 Piece	106,000 mm x 70,000 mm x 144,000 mm	128,000 g (0,000 g)	0,986 Cubic dec.

HALOPIN from OSRAM heralded a new modern generation of luminaires in terms of miniaturization and therefore set a standard that lamp and luminaire manufacturers throughout the world are still using. The ECO version of this lamp has a number of further benefits.

• Brilliant ECO accent lighting • Lower thermal output (compared with the standard reference product) opens up new design options • Incredibly small dimensions for revolutionary new luminaire designs • Robust filament design thanks to innovative, unique bulb pinch technology • Complies with IEC 60432-3 thanks to integrated fuse function, the lamp shuts down reliably • Approved for use in open luminaires to IEC 60598-1 • Simple handling thanks to G9 plug-in base/holder system • No transformer required • Average life: 2,000 h • Dimmable • Ra=100 • Color temperature: 20 W/33 W - 2,700 K; 48 W/60 W - 2,800 K • Design: two lengths 43 mm (short), 51 mm (long) • Base: G9 • UV filter

¹⁾ At 1 s on / 1 s off