

PN 750 V Plastisolert koblingsledning

PN 750V 50 G/G TR

H07V-R

Nexans ref.: 10022702**El. nummer:** 1066644 (1050446)**GTIN (EAN 13):** 7045210017656


Plastisolert koblingsledning

Beskrivelse

Til inntrekking i rør for skjult opplegg.



Standarder


Internasjonal EN 50265; HD 21.3;
IEC 60332-1**Norsk** NEK-HD 21.3Blyfri
JaMax.conductor temp.in service
70 °CRoHS conform
JaFlammehemmende
Ja

PN 750 V Plastisolert koblingsledning

PN 750V 50 G/G TR
Nexans ref.: 10022702

Egenskaper

Konstruksjonsegenskaper	
Kapfefarge	Gul/grønn
Ledertype	Flertrådet, rund
Ledermateriale	Glødd kobber
Isolasjon	Polyvinylklorid - PVC
Blyfri	Ja
Dimensjonsegenskaper	
Antall ledere	1
Antall enkelt tråder	7
Lederdiameter	8,7 mm
Nominell ytre diameter	11,5 mm
Vekt (ca.)	47,0 kg/100m
Ledertverrsnitt	50 mm ²
Bruksegenskaper	
Maks. tillatt ledertemperatur	70 °C
RoHS conform	Ja
Flammehemmende	Ja
Forpakning	Trommel


Blyfri
Ja

Max.conductor temp.in service
70 °C

RoHS conform
Ja

Flammehemmende
Ja