

H406121

Signallampe rød 24V Led

Artikkelnummer: XB4BVB4

El-nummer: 4303000

EAN13-nummer: 3389110891935

Signallampe rød 24V Led

Technical information

Tilleggsinformasjon

sale per indivisible quantity

1

knappens tilleggs info.

with plain lens

Sertifikater og standarder

Standarder

EN/IEC 60947-1

EN/IEC 60947-5-1

EN/IEC 60947-5-4

EN/IEC 60947-5-5

JIS C 4520

UL 508

CSA C22.2 No 14

CSA

UL listet

Produktsertifikater

Tilkoblinger

tilkoblinger - terminaler

skrutilkobling: $\leq 2 \times 1.5 \text{ mm}^2$ med endehylse conforming to EN/IEC 60947-1

skrutilkobling: $1 \times 0.22...2 \times 2.5 \text{ mm}^2$ uten endehylse conforming to EN/IEC 60947-1

Elektrisk

[U_i] rated insulation voltage

250 V (degree of pollution: 3) conforming to EN 60947-1

[U_{imp}] rated impulse withstand voltage

4 kV conforming to EN 60947-1

[U_s] merkespenning

24 V AC/DC, 50/60 Hz

Spenningsgrenser

19.2...30 V DC

21.6...26.4 V AC

Strømforbruk

18 mA mA

motstand mot spenningsvariasjon

1 kV conforming to IEC 61000-4-5

Miljø

protective treatment

TH

omgivelsestemperatur for oppbevaring

-40...70 °C °C

ambient air temperature for operation

-25...70 °C °C

class of protection against electric shock

klasse I conforming to IEC 60536

IP-grad

IP66 conforming to IEC 60529

NEMA beskyttelsesgrad

NEMA 13

NEMA 4X

IK beskyttelsesklasse

IK05 conforming to IEC 50102

Vibrasjonsmotstand

5 gn (f = 12...500 Hz) conforming to IEC 60068-2-6

30 gn (duration = 18 ms) for half sine wave acceleration

conforming to IEC 60068-2-27

50 gn (duration = 11 ms) for half sine wave acceleration

conforming to IEC 60068-2-27

resistance to fast transients

2 kV conforming to IEC 61000-4-4

resistance to electromagnetic fields

10 V/m conforming to IEC 61000-4-3

resistance to electrostatic discharge

6 kV on contact (on metal parts) conforming to IEC 61000-4-2

8 kV in free air (in insulating parts) conforming to IEC 61000-4-2

klasse B conforming to IEC 55011

electromagnetic emission

Praktisk

Klemmebeskrivelse ISO n°1

(X1-X2)PL

linsetype

rød

Signaltype

klar

Lampeholder	innebygget LED
Ytelse	
service life	100000 h at rated voltage and 25 °C
Fysiske mål	
fixing collar material	zamak
Høyde	47 mm mm
Bredde	30 mm mm
Dybde	54 mm mm
Vekt	0.08 kg kg
motstandsdyktig mot høytryksspyling	7000000 Pa at 55 °C,distance: 0.1 m
shape of signaling unit head	Rund
Produktmerking	
Produktspekter	Harmony XB4
Produkt eller komponent type	complete pilot light
kallenavn på utstyr	XB4
Kant materiale	forkrommet metall
Montasjediameter	22 mm mm
lyskilde	protected LED
lyskildefarge	Rød

Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: kundesenter@no.schneider-electric.com