



Rated starting time

Product description: 64401

64401

Product code: 4008321393845

Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog: http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321393845

O	
Capabilities Dimmable	Yes
Burning position	Any
Country specific categorizations	
ILCOS	HSGST/C/UB-100-230-E27
Certificates & standards	
EEI - Energy Label	С
Additional product data	
Base (standard designation)	E27
New article	NEW
Design / version	Tube
Colors & materials	
Rated lamp mercury content	0.0 mg
Mercury-free	Yes
Electrical data	
Rated wattage	100 W
Nominal wattage	100 W
Nominal voltage	230 V
Rated number of switching cycles	1000000 1)
Rated power factor \(\lambda \)	1.00
Discouries 0 weight	
Dimensions & weight	405.0
Length	105.0 mm
Overall length	105.0 mm
Diameter	32.0 mm
Light center length (LCL)	75.0 mm
Outer bulb	T30
Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h
reaced ramp line time	2000 11
Light technical data	
Nominal luminous flux	1800 lm
Rated luminous flux	1800 lm
Rated color temperature	2900 K
Rated color rendering index Ra	100

0.0 s



64401

Light technical data				
Rated warm-up time (60 %)	0 s			
Lumen main.fact.at end of nom.life time	0.80			

Packaging units						
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume		
4008321393845	Folding carton box contains 1 Piece	42,000 mm x 42,000 mm x 111,000 mm	74,800 g (0,000 g)	0,196 Cubic dec.		
4008321393852	Shipping carton box contains 12 Piece	140,000 mm x 127,000 mm x 180,000 mm	984,600 g (0,000 g)	3,200 Cubic dec.		

HALOLUX ECO: The compact package from OSRAM
HALOLUX CERAM ECO is so slim it is perfect for narrow compact luminaires. It is available in wattages up to 205 W and can be operated without a transformer. It is characterized by its pure natural halogen light and is therefore the perfect high-performance lamp for modern sophisticated luminaires.

• More compact dimensions than ordinary light bulbs • Available in a higher wattages up to 205 W • 100 % dimmable • The same pleasant quality of light as that of an incandescent lamp • Average life of 2,000 hours • No transformer required • UV filter

1) At 1 s on / 1 s off