

H403725

Kontaktelement 1nc

Artikkelnummer: ZB2BE102

El-nummer: 4316345

EAN13-nummer: 3389110612615

Technical information

Sertifikater og standarder

Standarder

EN/IEC 60204-32

EN/IEC 60947-5-1

UL 508

CSA C22.2 No 14

Kompatibilitet

Produktkompatibilitet

XACA

XB4

XB5

Tilkoblinger

tilkoblinger - terminaler

screw clamps terminals (1 x 2.5 mm²)with or without cable end

screw clamps terminals (2 x 1.5 mm²)with or without cable end

Elektrisk

Kontakt angivelse

A600 AC-15, Ue = 240 V, Ie = 3 A conforming to IEC 947-5-1 appendix A

A600 AC-15, Ue = 600 V, Ie = 1.2 A conforming to IEC 947-5-1 appendix A

Q600 DC-13, Ue = 250 V, Ie = 0.27 A conforming to IEC 947-5-1 appendix A

Q600 DC-13, Ue = 600 V, Ie = 0.1 A conforming to IEC 947-5-1 appendix A

[Ithe] conventional enclosed thermal current

10 A A

[Ui] rated insulation voltage

600 V (degree of pollution: 3) conforming to IEC 60947-1

[Uimp] rated impulse withstand voltage

6 kV conforming to IEC 60947-1

Resistanse over teminaler

<= 25 MOhm MOhm

short circuit protection

med sikring by 10 A gG (gl) cartridge fuse

nominell forbrukt effekt drift W

40 W DC-13 for 1000000 cycles, operating rate: 3600 cyc/h at

120 V, load factor = 0.5 conforming to IEC 60947-5-1

48 W DC-13 for 1000000 cycles, operating rate: 3600 cyc/h at 48

V, load factor = 0.5 conforming to IEC 60947-5-1

65 W DC-13 for 1000000 cycles, operating rate: 3600 cyc/h at 24

V, load factor = 0.5 conforming to IEC 60947-5-1

Miljø

ambient air temperature for operation

-25...70 °C °C

ambient air temperature for storage

-40...70 °C °C

Vibrasjonsmotstand

15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6

Støtmotstand

100 gn conforming to IEC 60068-2-27

class of protection against electric shock

klasse II

Praktisk

kontaktblokk applikasjon

en hastighet

Type arm/stempel

fjærretur

contacts type and composition

1 NC

contacts operation

slow-break

operating force

13...15 N N

Klemmebeskrivelse ISO n°1

(11-12)NC

Installasjon

montering av blokk

montering i front

Ytelse

mechanical durability

1000000 cycles cycles

Fysiske mål

Vekt	0.02 kg kg
 Produktmerking	
Produktspekter	Harmony XAC
Produkt eller komponent type	kontaktblokk
Type komponent	ZB2
type kontaktblokk	Enkel
 Anvendelse/bruk	
Elektrisk krets-type	styrekrets

Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: kundesenter@no.schneider-electric.com