


SLIM EVO Proiettori LED • LED floods


QUALIKO




SLIM EVO 10
864 Lumen



SLIM EVO 30
2448 Lumen



SLIM EVO 50
4227 Lumen



Type	Part N°	Dimensions	Weight kg	Lumen	°Kelvin	Input Voltage (V)	Power (W max)	Power Factor	Packing box Dimensions (mm)
SLIM EVO 10 White	BFL101EVO10B	113xx81x35	0,31	864	4000	200+240	10	>0,9	131x123x40
SLIM EVO 30 White	BFL101EVO30B	185x135x35	0,75	2448	4000	200+240	30	>0,9	203x170x40
SLIM EVO 50 White	BFL101EVO50B	215x155x35	0,99	4227	4000	200+240	50	>0,9	245x194x40

Proiettore LED

- Proiettore orientabile LED ad alta luminosità
- Nuovo design semplice, pulito, discreto. Adatto anche per usi interni
- Scocca in alluminio pressofuso, colore bianco
- Grado di protezione IP65
- CRI >80

de interior o exterior

- Cuerpo en aluminio fundido IP65, acabado en pintura epoxy blanco
- CRI >80

LED Flood

- High flux LED flood
- New clean minimal design. Suitable both for indoor and outdoor
- IP 65 die cast aluminium body, painted in white epoxy
- CRI >80

LED Projektor

- High Power schwenkbar Projektor
- Neu und klares Design - Auch für Inneninstallation geeignet
- Gussaluminiumkörper, Weiss
- Schutzgrad IP 65
- CRI >80

Projecteur LED

- Projecteur orientable LED haute luminosité
- Nouveau design simple, net, discret.
- Adapté également à l'usage interne
- Corps en aluminium moulé sous pression, disponible en blanc
- Degré de protection IP65
- CRI >80

Proyector LED

- Proyector LED de alto flujo lumínico
- Nuevo diseño sencillo y minimalista. Apropiado para aplicaciones

