

Damp area small distributor IP65, 1-row

Order number: 7240026

Type: APV4



- Robuste Ausführung aus schlagzähem Kunststoff
- Wechselbare Einzeltüren in rauchtopas für Rechts- und Linksanschlag
- Ideal für schwierige Installationsumgebungen in Industrieanlagen, Werkstätten, Kellern oder Garagen
- Für Anwendungen im geschützten Außenbereich, der Schutzart entsprechend geeignet
- Für Anwendungen im ungeschützten Außenbereich muss das Gehäuse vor witterungsbedingter Beanspruchung durch Einbau in ein Outdoorgehäuse geschützt werden

suitable for:

Dimensions

Depth	120 mm
Height	197 mm
Width	122.5 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Box material	PS
Door material	

Properties

Can be lead sealed	true
Colour	Grey
Degree of protection (IP)	IP65
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Number of compartments	4
Number of rows	1
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Total inserts	

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
VDE	-

Accessories

Equipped with	1x cover strip 4TE 1x PE screw terminal 5-pole 1x N screw terminal 5-pole double membrane seals (DMS20 / DMS25)
---------------	--