

H406084

Trykknapphode opphøyet gul

Artikkelnummer: ZB4BL5

El-nummer: 4302668

EAN13-nummer: 3389110887808

Technical information

Tilleggsinformasjon

sale per indivisible quantity

1

Sertifikater og standarder

Standarder

EN/IEC 60947-1

EN/IEC 60947-5-1

EN/IEC 60947-5-4

EN/IEC 60947-5-5

JIS C 4520

UL 508

CSA C22.2 No 14

Produktsertifikater

BV

CSA

DNV

GL

LROS (Lloyds register of shipping)

RINA

UL listet

Miljø

protective treatment

TH

ambient air temperature for storage

-40...70 °C °C

ambient air temperature for operation

-25...70 °C °C

class of protection against electric shock

klasse I conforming to IEC 60536

IP-grad

IP66 conforming to IEC 60529

NEMA beskyttelsesgrad

NEMA 13

NEMA 4X

IK beskyttelsesklasse

IK03 conforming to IEC 50102

Vibrasjonsmotstand

5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6

30 gn (duration = 18 ms) for half sine wave acceleration

conforming to IEC 60068-2-27

50 gn (duration = 11 ms) for half sine wave acceleration

conforming to IEC 60068-2-27

Praktisk

Type arm/stempel

fjærretur

operator profile

gul projecting umerket

electrical composition code

C1 for <= 9 contacts using single blocks in front mounting

C2 for <= 9 contacts using single and double blocks in front mounting

C11 for <= 3 contacts using single blocks in front mounting

C15 for 1 contacts using single blocks in front mounting

Ytelse

mechanical durability

5000000 cycles cycles

Fysiske mål

Bredde

29 mm mm

Høyde

29 mm mm

Dybde

33 mm mm

shape of signaling unit head

Rund

Produktmerking

Produktspekter

Harmony XB4

Produkt eller komponent type

head for non-illuminated pushbutton

kallenavn på utstyr

ZB4

Kant materiale

forkrommet metall

Montasjediometer

22 mm mm

Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: kundesenter@no.schneider-electric.com