

SPIRAL CABLES

Spiral cables PVC

Leads: PVC, sheath: PVC, elongation factor 1:4, 70°C

- End 1/end 2: 200 mm each, cut flush
- Properties: good value, low mechanical resistance, medium chemical resistance, medium reset force
- Examples of use: lamps, IT systems and mobile devices/equipment

Art. no.	Coil length	Operating length	Version	Unit
Spiral cable				
H05W-F 3G 1.50 mm ² , diameter approx. 8.4 mm, WID: approx. 10 mm, WAD: approx. 27 mm				
654.180	500 mm	2,000 mm	- Black	50 items
654.280	500 mm	2,000 mm	- White	50 items
654.181	1,000 mm	4,000 mm	- Black	30 items
654.281	1,000 mm	4,000 mm	- White	30 items
654.182	1,500 mm	6,000 mm	- Black	15 items
654.282	1,500 mm	6,000 mm	- White	15 items

Spiral cable, PUR

Leads: PVC, sheath: PUR, elongation factor 1:5, 70°C

- End 1/end 2: 200 mm each, cut flush
- Properties: good chemical resistance, good resistance to cold, excellent abrasion and notching resistance, very good reset force
- Examples of use: connecting cables for engineering, the construction industry or robotics

Art. no.	Coil length	Operating length	Version	Unit
Spiral cable, PUR				
YMH11Y-J 3G 1.50 mm ² , diameter approx. 8.0 mm, WID: approx. 13 mm, WAD: approx. 29 mm				
692.180	500 mm	2,500 mm	- Black	30 items
692.280	500 mm	2,500 mm	- White	30 items
692.181	1,000 mm	5,000 mm	- Black	20 items
692.281	1,000 mm	5,000 mm	- White	20 items
692.182	1,500 mm	7,500 mm	- Black	15 items
692.282	1,500 mm	7,500 mm	- White	15 items

