

H603969

Tidsblokk 0,1-3s fors.inn

Artikkelnummer: LADT0

El-nummer: 4176526

EAN13-nummer: 3389110385021

Tilbehør til Tesys D kontaktorer

Technical information

Sertifikater og standarder

Standarder

BS 4794
EN 60947-5-1
IEC 60947-5-1
NF C 63-140
VDE 0660
CSA
UL

Produktsertifikater

Kompatibilitet

sikringsstørrelse

10 A gG IEC 60947-5-1

Tilkoblinger

tilkoplinger - terminaler

skrutilkobling 1 cable 1...2.5 mm² - cable stiffness: fleksibel - med cable end
skrutilkobling 1 cable 1...2.5 mm² - cable stiffness: fleksibel - uten cable end
skrutilkobling 1 cable 1...2.5 mm² - cable stiffness: helkjernet - med cable end
skrutilkobling 1 cable 1...2.5 mm² - cable stiffness: helkjernet - uten cable end
skrutilkobling 2 cable 1...2.5 mm² - cable stiffness: fleksibel - med cable end
skrutilkobling 2 cable 1...2.5 mm² - cable stiffness: fleksibel - uten cable end
skrutilkobling 2 cable 1...2.5 mm² - cable stiffness: helkjernet - med cable end
skrutilkobling 2 cable 1...2.5 mm² - cable stiffness: helkjernet - uten cable end

Elektrisk

pole contact composition

1 NO + 1 NC

[Ui] rated insulation voltage

690 V - conforming to IEC 60947-5-1
600 V - certifications CSA
600 V - certifications UL

[Ue] merkespenning

690 V AC 25...400 Hz

[I_{th}] conventional free air thermal current

10 A at ≤ 60 °C

I_{rms} rated making capacity

140 A at ≤ 690 V AC conforming to IEC 60947-5-1
250 A at ≤ 690 V DC conforming to IEC 60947-5-1

permissible short-time rating

100 A at -5...60 °C 1 s
120 A at -5...60 °C 500 ms
140 A at -5...60 °C 100 ms

minimum brytestrøm

5 mA

minimum switching voltage

17 V

Isolasjonsmotstand

> 10 MOhm

Miljø

environmental characteristic

normale omgivelser

IP-grad

IP2x conforming to VDE 0106

protective treatment

TH conforming to IEC 60068

ambient air temperature for operation

-5...60 °C °C

ambient air temperature for storage

-60...80 °C °C

operating altitude

3000 m uten derating in temperature

Praktisk

non-overlap time	1.5 ms on de-energisation (no overlap between NC and NO contact)
Område - tidsforsinkelse	1.5 ms on energisation (no overlap between NC and NO contact)
► Installasjon	0.1...0.3 s
monteringsområde	front
► Ytelse	
protection type	gG fuse <= 10 A rating according to operational current for Ue <= 690 V
mechanical durability	5 Mcycles cycles
► Fysiske mål	
Vekt	0.06 kg kg
► Produktmerking	
range	TeSys
Produkt eller komponent type	time delay auxiliary contact block
timer type	forsinket inn

Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: kundesenter@no.schneider-electric.com