

H406048

Trykknapp sort 1no

Artikkelnummer: XB4BA21

El-nummer: 4303264

EAN13-nummer: 3389110886948

"Trykknapper og LED lamper Ø 22mm i metall. IP66 som standard. Enkel og rask montasje. Konseptet for ""Klikk-på"" montasje er så pålitelig at bare en skrue er nødvendig for montering og den forenkler og reduserer tiden for montasje vesentlig."

Technical information

Tilleggsinformasjon

sale per indivisible quantity

1

Sertifikater og standarder

Standarder

CSA C22.2 No 14

EN/IEC 60947-1

EN/IEC 60947-5-1

EN/IEC 60947-5-4

EN/IEC 60947-5-5

JIS C 4520

UL 508

Produktsertifikater

BV

CSA

DNV

GL

LROS (Lloyds register of shipping)

RINA

UL listet

Tilkoblinger

tilkoblinger - terminaler

skrutilkobling: $\leq 2 \times 1.5 \text{ mm}^2$ med endehylse conforming to EN/IEC 60947-1

skrutilkobling: $1 \times 0.22 \dots 2 \times 2.5 \text{ mm}^2$ uten endehylse conforming to EN/IEC 60947-1

Elektrisk

short circuit protection

10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1

[Ith] conventional free air thermal current

10 A conforming to EN/IEC 60947-5-1

[Ui] rated insulation voltage

600 V (degree of pollution: 3) conforming to EN/IEC 60947-1

[Uimp] rated impulse withstand voltage

6 kV conforming to EN/IEC 60947-1

[Ie] rated operational current

3 A at 240 V, AC-15, A600 conforming to EN/IEC 60947-5-1

6 A at 120 V, AC-15, A600 conforming to EN/IEC 60947-5-1

0.1 A at 600 V, DC-13, Q600 conforming to EN/IEC 60947-5-1

0.27 A at 250 V, DC-13, Q600 conforming to EN/IEC 60947-5-1

0.55 A at 125 V, DC-13, Q600 conforming to EN/IEC 60947-5-1

1.2 A at 600 V, AC-15, A600 conforming to EN/IEC 60947-5-1

Miljø

protective treatment

TH

ambient air temperature for storage

-40...70 °C °C

ambient air temperature for operation

-25...70 °C °C

class of protection against electric shock

klasse I conforming to IEC 60536

IP-grad

IP66 conforming to IEC 60529

NEMA beskyttelsesgrad

NEMA 13

NEMA 4X

IK beskyttelsesklasse

conforming to IEC 50102

Vibrasjonsmotstand

5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6

30 gn (duration = 18 ms) for half sine wave acceleration

conforming to IEC 60068-2-27

50 gn (duration = 11 ms) for half sine wave acceleration

conforming to IEC 60068-2-27

Praktisk

Klemmebeskrivelse ISO n°1	(13-14)NO
Type arm/stempel	fjærretur
operator profile	Svart innfelt umerket
contacts type and composition	1 NO
contacts operation	slow-break
contacts usage	standard kontakt
Positiv åpning	uten positive opening
operating travel	2.6 mm (NO changing electrical state)
	4.3 mm (total travel)
operating force	3.8 N (NO changing electrical state)
Ytelse	
mechanical durability	5000000 cycles cycles
Elektrisk levetid	1000000 cycles AC-15 2 A 230 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C
	1000000 cycles DC-13 0.2 A 110 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C
	1000000 cycles AC-15 3 A 120 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C
	1000000 cycles AC-15 4 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C
	1000000 cycles DC-13 0.5 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C
	$\lambda < 10\exp(-6)$ at 5 V, 1 mA in clean environment conforming to EN/IEC 60947-5-4
	$\lambda < 10\exp(-8)$ at 17 V, 5 mA in clean environment conforming to EN/IEC 60947-5-4
elektrisk funksjonalitet i h.h.t. IEC 60947-5-7	
Fysiske mål	
fixing collar material	zamak
Høyde	47 mm mm
Bredde	30 mm mm
Dybde	52 mm mm
Vekt	0.08 kg kg
motstandsdyktig mot høytryksspyling	7000000 Pa at 55 °C,distance: 0.1 m
shape of signaling unit head	Rund
Tiltrekkningsmoment	0.8...1.2 N.m conforming to EN 60947-1
shape of screw head	kryss Philips no 1
	kryss Pozidriv No 1
	hullet flat Ø 4 mm
	hullet flat Ø 5.5 mm
contacts material	silver alloy (Ag/Ni)
Produktmerking	
Produktspekter	Harmony XB4
Produkt eller komponent type	complete push-button
kallenavn på utstyr	XB4
Kant materiale	forkrommet metall
Montasjediameter	22 mm mm

Supplier information

Leverandør: Schneider Electric Norge AS
Adresse: Deliveien 10, 1540 Vestby

Fax: + 47 64 98 57 01
Telefon: +47 64 98 56 00

Web: <http://www.schneider-electric.no>
e-Post: kundesenter@no.schneider-electric.com