



Product description: 64820 FL 35W 240V GU10 20X1 OSRAM ¹⁾
Product code: 4050300727226
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300727226

Capabilities				
Dimmable	Yes			
Burning position	Any			
Additional product data				
Base (standard designation)	GU10			
Design / version	Reflector			
Colors & materials				
Rated lamp mercury content	0.0 mg			
Mercury-free	Yes			
Electrical data				
Rated wattage	35 W			
Nominal wattage	35 W			
Nominal voltage	240 V			
Rated number of switching cycles	1000000 ²⁾			
Rated power factor λ	1.00			
Dimensions & weight				
Length	55.0 mm			
Overall length	53.0 mm			
Diameter	51.0 mm			
Outer bulb	PAR51			
Lifespan				
Nominal lamp life time	2000 h			
Rated lamp life time	2000 h			
Light technical data				
Luminous intensity	570 cd			
Beam angle	35 °			
Rated color temperature	2700 K			
Rated color rendering index Ra	100			
Rated starting time	0.0 s			
Rated warm-up time (60 %)	0 s			
Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300727226	Folding carton box contains 1 Piece	50,000 mm x 50,000 mm x 63,000 mm	39,667 g (0,000 g)	0,158 Cubic dec.
4050300727240	Shipping carton box contains 20 Piece	111,000 mm x 130,000 mm x 257,000 mm	1 036,800 g (0,000 g)	3,771 Cubic dec.



The OSRAM HALOPAR 16 gives luminaire manufacturers a lamp that drastically reduces construction costs for dichroic reflector luminaires. The fully dimmable OSRAM HALOPAR 16 can be simply operated on line voltage and is ideal wherever installing transformers would be prohibitively expensive or impossible. There is a choice of reflector - either the faceted aluminum reflector or the decorative shimmering dichroic reflector.

• Brilliant accent light • With whole glass reflector for brilliant lighting effect • Innovative bulb pinch technology for the burner and with integrated fuse function; complies with the safety requirements of IEC 60432-3 • Approved for use in open luminaires to IEC 60598-1 • Robust filament design thanks to innovative, unique bulb pinch technology • No transformer required • Average life: 2,000 h • Dimmable • $R_a=100$ • Color temperature: 35 W GU10 - 2,700 K; 50 W GU10 - 2,800 K; 50 W GZ10 - 3,000 K • Base: GU10, GZ10 • UV filter
For light distribution curves go to www.osram.com

1) Not suitable for outdoor use or damp conditions

2) At 1 s on / 1 s off