

H430583

Endebryter kort arm/stålrulle

Artikkelnummer: XCKJ10513

El-nummer: 4300545

EAN13-nummer: 3389110645811

Technical information

Sertifikater og standarder

Produktsertifikater

CCC

CSA

UL

Standarder

CENELEC EN 50041

EN 60204-1

EN 60947-5-1

IEC 60204-1

IEC 60947-5-1

UL 508

CSA C22.2 No 14

Tilkoblinger

Elektrisk tilkobling

screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm²

Kabelinngang

1 entry tapped for Pg 13.5 cable gland, cable outer diameter:

9...12 mm

Elektrisk

antall poler

2

[I_e] rated operational current

3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1

appendix A

0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1

appendix A

[I_{the}] conventional enclosed thermal current

10 A A

[U_i] rated insulation voltage

300 V conforming to UL 508

300 V conforming to CSA C22.2 No 14

500 V degree of pollution 3 conforming to IEC 60947-1

Resistanse over teminaler

<= 25 MOhm conforming to IEC 60255-7 category 3

[U_{imp}] rated impulse withstand voltage

6 kV conforming to IEC 60664

6 kV conforming to IEC 60947-1

short circuit protection

10 A by gG cartridge sikring

Miljø

Støtmotstand

50 gn (duration = 11 ms) conforming to IEC 60068-2-27

Vibrasjonsmotstand

25 gn (f = 10...500 Hz) conforming to IEC 60068-2-6

IP-grad

IP66 conforming to IEC 60529

IK beskyttelsesklasse

IK07 conforming to EN 50102

class of protection against electric shock

conforming to IEC 61140

conforming to NF C 20-030

ambient air temperature for operation

-25...70 °C °C

ambient air temperature for storage

-40...70 °C °C

protective treatment

TC

Praktisk

Bevegelse av hode

dreie

Type arm/stempel

spring return roller lever metall

Bryter påvirkning

med 30° kam

Tilnærmings type

lateral approach 1 or 2 programmable direction

contacts type and composition

1 NC + 1 NO

Kontaktens isolasjonsform

Zb

contacts operation

momentan

Antall trinn

1

Positiv åpning

med

positive opening minimum torque	0.5 N.m N.m
Maksimum aktiverings hastighet	1.5 m/s
Klemmebeskrivelse ISO n°1	(13-14)NO (21-22)NC
 Installasjon	
festemetode	med kropp
 Ytelse	
Elektrisk levetid	5000000 cycles, DC-13, induktiv load type, 120 V, 4 W, operating rate: <= 60 cyc/mn, load factor: 0,5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13, induktiv load type, 24 V, 10 W, operating rate: <= 60 cyc/mn, load factor: 0,5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13, induktiv load type, 48 V, 7 W, operating rate: <= 60 cyc/mn, load factor: 0,5 conforming to IEC 60947-5-1 appendix C
mechanical durability	30000000 cycles cycles
 Fysiske mål	
Materiale	metall
Materiale kropp	zamak
Materiale hode	zamak
minimum torque for tripping	0.25 N.m N.m
Bredde	40 mm mm
Høyde	77 mm mm
Dybde	44 mm mm
Vekt	0.49 kg kg
 Produktmerking	
Produktspekter	OsiSense XC
Serie navn	standard størrelse
Produkt eller komponent type	limit switch
kallenavn på utstyr	XCKJ
Sensor design	form A conforming to CENELEC EN 50041
type kropp	fast
Hode type	dreie hode

Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: kundesenter@no.schneider-electric.com