

Anbaugerätestecker
Bestellnr. 480




- Schraubkontakt
- mit Klappdeckel

Technische Daten

Ampere	63 A
Pole	5 p
Volt	400 V
Uhrzeitstellung	6 h
Hertz	50-60 Hz
Anschluss technik	Schraubkontakt
Kontakt	standard
Schutzart	IP 67
Gewicht	791 g
Prüfzeichen	DE,VDE

Abmessungen



Zeichnung	Amp.	16				32		63			
2 MB 40	Pole	5	3	4	5	4	5	4	5	4	5
Maße in mm											
a		85	85	85	85	114	114	114	114	114	114
b		85	85	85	85	114	114	114	114	114	114
c		141	141	141	144	180	180	180	180	180	180
d		70	70	70	70	90	90	90	90	90	90
e		70	70	70	70	90	90	90	90	90	90
f		6,2	6,2	6,2	6,2	6,2	6,2	6,2	6,2	6,2	6,2
g		6	6	6	6	6	6	6	6	6	6
g.1		2	2	2	2	2	2	2	2	2	2
h		181	181	181	188	242	242	242	242	242	242
s		86	93	93	100	113	113	113	113	113	113
l		30	30	30	30	40	40	40	40	40	40
Klemmen für Leiterquer-											
schnitt von bis mm²											
		—2,5	—6	—6	—6	—16	—16	—16	—16	—16	—16