

Project document

Dokument dato: 6/18/2013
Prosjekt navn:
Avdeling / Seksjon:
Adress:
Utsteder:
Revisjon:
Annen informasjon:

Project document content

Artikkelnummer:	Description	El-nummer:	EAN13-nummer:
ZCKJ1	ENDEBRYTERKROP	4317710	3389110646108

Supplier information

Leverandør: Schneider Electric Norge AS	Fax: + 47 64 98 57 01	Web: http://www.schneider-electric.no
Adresse: Deliveien 10, 1540 Vestby	Telefon: +47 64 98 56 00	e-Post: kundesenter@no.schneider-electric.com

H404609

ENDEBRYTERKROP

Artikkelnummer: ZCKJ1

El-nummer: 4317710

EAN13-nummer: 3389110646108

Technical information

Kompatibilitet

Produktkompatibilitet

XCKJ

Tilhørende hode

ZCKE05

ZCKE06

ZCKE08

ZCKE21

ZCKE23

ZCKE61

ZCKE619

ZCKE62

ZCKE629

ZCKE63

ZCKE64

ZCKE65

ZCKE66

ZCKE67

Tilkoblinger

Elektrisk tilkobling

screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm²

Kabelinngang

1 entry tapped for Pg 13.5 cable gland

Elektrisk

antall poler

2

[Ie] rated operational current

3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A

0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A

[Ithe] conventional enclosed thermal current

10 A A

[Ui] rated insulation voltage

300 V conforming to CSA C22.2 No 14 contact block

300 V conforming to UL 508 kontaktblokk

500 V degree of pollution 3 conforming to IEC 60947-1 kontaktblokk

Resistanse over teminaler

0.25 mOhm conforming to IEC 60255-7 category 3

[Uimp] rated impulse withstand voltage

6 kV conforming to IEC 60664

6 kV conforming to IEC 60947-1

short circuit protection

10 A by gG cartridge sikring

Miljø

IP-grad

IP65

IK beskyttelsesklasse

IK08

ambient air temperature for operation

-25...70 °C for standard environment

10...120 °C for high temperature

-40...70 °C for low temperature

ambient air temperature for storage

-40...120 °C °C

environmental characteristic

high temperature

lav temperatur

standard environment

Praktisk

local display

uten

contacts type and composition

1 NC + 1 NO

contacts operation

momentan

Antall trinn

1 1 position

Positiv åpning	med
Minimum aktiverings hastighet	0.01 m/min m/s
Klemmebeskrivelse ISO n°1	(13-14)NO (21-22)NC
► Ytelse	
Elektrisk levetid	5000000 cycles, DC-13 120 V, 4 W, operating rate: < 60 cyc/mn, load factor: 0,5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate: < 60 cyc/mn, load factor: 0,5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0,5 conforming to IEC 60947-5-1 appendix C
► Fysiske mål	
Materiale kropp	Metall
contacts material	silver plated contacts
Bredde	40 mm mm
Høyde	77 mm mm
Dybde	44 mm mm
Vekt	0.31 kg kg
► Produktmerking	
Produktspekter	OsiSense XC
Serie navn	standard størrelse
Produkt eller komponent type	limit switch body
kallenavn på utstyr	ZCKJ
type kropp	fast

Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: kundesenter@no.schneider-electric.com