



Ref. No. 831035

Description: ARIA 43 cabinet with double bit lock 3 mm one point closing system

EAN 5412348310355

Products > Boxes & Cabinets & Pedestals > Enclosures for indoor and outdoor

- The cabinets are made of light-grey (RAL 7035) hot moulded, glass fibre reinforced polyester, dyed in mass. The enclosure is furnished with four threaded studs and bolts for mounting plate or mounting frame
- The enclosure provides total insulation and a protection degree of IP66 following IEC 60529 and EN 60529.
- Protection degree IK10 against external mechanical impacts according to EN 62262 and IEC 62262 (IK07 for cabinets with glazed door).
- This protection covers the total volume of the enclosure according to EN 62208 and IEC 62208.
 Resists temperatures up to 70°C in continuous use (peak temperatures up to 150°C).
 Self extinguishing and halogen-free.

- Cabinets are maintenance free and corrosion resistant.
- Rated insulation voltage Ui = 1000V.

Descriptors	
Category	Enclosures for indoor and outdoor
Family Name	ARIA
IK	IK10

Specifications	
Enclosure type	Cabinet
Total Insulation	Yes
Raw materials	Polyester glass-fibre reinforced hot-moulded
Ambient conditions	Indoor, Outdoor
Installation	Pole Fixing, Wall mounting
IP	IP66
Product/Accessory	Product
Product/Accessory functionality	Cabinet
Door/Cover	Door
Door/Cover- plain/glazed	Plain
Standards	EN 60439-1, EN 60529, EN 62208, IEC 60439-1, IEC 60529, IEC 62208
Туре	ARIA 43
Inner height	375 mm
Inner width	270 mm
Kind of closing system	With double bit lock 3 mm 1-point closing system
Screws/Hinges/Bolts	Hinges
Colour	RAL 7035
Standard packing	1

Classifications		
Approvals	AS, CSA, UL	
ETIM 5.0	EC000058	
ETIM 6.0	EC000058	

uk.geindustrial.com Created on: 15/05/2017

Dimensions		
Volume	0.020400 m3	
Height	400.0 mm	
Width	300.0 mm	
Depth	170.0 mm	

uk.geindustrial.com Created on: 15/05/2017