



Product number 1198350
EAN 4007123022878

DESCRIPTION

- Reel body made from rust-resistant and galvanised sheet steel fitted to a particularly sturdy galvanised steel tube frame.
- Innovative and ergonomic cable guide handle „cable pilot“ for perfect cable-management during winding. Handle commutes on both sides and allows easy carrying and cable storage. For right and left handed easy to rewind.
- Rotary handle for comfortable rolling up.
- RN cable is very robust, oil resistant and especially suited for professional use and on site.
- 3 water-jet protected earthed socket outlets with self-closing protective caps.
- Thermal cut-out protection, indicator shows overheating or overloading. Patent pending.

TECHNICAL DATA

Cable quality	Rubber-Neoprene	Plug system CEE socket	Without
Product number	1198350	Plug system socket	Type F (Protective contact)
Cable length	25 m	Plug system plug	Type E and F (Protective contact with earth hole)
Cable designation	H07RN-F 3G2,5	Max. current carrying capacity	16 A
Cable colour	black	Nominal input voltage	230 V
Reel diameter	290 mm	Degree of protection (IP)	IP44

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1	Weight of product (including packaging)	7.01 kg
Weight of product (without packaging)	7 kg	Dimension LxWxH (incl. packing)	19.5 cm x 29.5 cm x 37 cm
Dimension LxWxH (without packing)	19 cm x 29 cm x 37 cm		