

H404748

ENDEBRYTERKROPP

# Artikkelnummer: ZCKS2

El-nummer: 4307582

EAN13-nummer: 3389110645842

## Technical information

### Kompatibilitet

Produktkompatibilitet

XCKS

Tilhørende hode

ZCKD029

ZCKD01

ZCKD019

ZCKD02

ZCKD05

ZCKD06

ZCKD08

ZCKD31

ZCKD33

ZCKD34

ZCKD39

ZCKD41

ZCKD49

ZCKD54

ZCKD55

ZCKD59

ZCKD81

ZCKD91

### Tilkoblinger

Elektrisk tilkobling

screw-clamp terminals, clamping capacity: 1 x 0.75...2 x 1.5 mm<sup>2</sup>

Kabelinngang

1 entry tapped for Pg 13.5 cable gland

### Elektrisk

antall poler

2

[Ie] rated operational current

3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A

0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A

[Ithe] conventional enclosed thermal current

10 A A

[Ui] rated insulation voltage

300 V conforming to CSA C22.2 No 14 contact block

300 V conforming to UL 508 kontaktblokk

500 V degree of pollution 3 conforming to IEC 60947-1 kontaktblokk

Resistanse over teminaler

0.25 mOhm conforming to IEC 60255-7 category 3

[Uimp] rated impulse withstand voltage

6 kV conforming to IEC 60664

6 kV conforming to IEC 60947-1

short circuit protection

10 A by gG cartridge sikring

### Miljø

IP-grad

IP65

IK beskyttelsesklasse

IK08

ambient air temperature for operation

-25...70 °C for standard environment

ambient air temperature for storage

-40...70 °C °C

environmental characteristic

standard environment

### Praktisk

local display

uten

contacts type and composition

2 C/O

contacts operation

momentan

Antall trinn

1 1 position

|                               |                |
|-------------------------------|----------------|
| Positiv åpning                | uten           |
| Minimum aktiverings hastighet | 0.01 m/min m/s |
| Klemmebeskrivelse ISO n°1     | (11-12)NC      |
|                               | (13-14)NO      |
|                               | (21-22)NC      |
|                               | (23-24)NO      |

## ► Ytelse

Elektrisk levetid

5000000 cycles, DC-13 120 V, 4 W, operating rate: < 60 cyc/mn,  
load factor: 0,5 conforming to IEC 60947-5-1 appendix C  
5000000 cycles, DC-13 24 V, 10 W, operating rate: < 60 cyc/mn,  
load factor: 0,5 conforming to IEC 60947-5-1 appendix C  
5000000 cycles, DC-13 48 V, 7 W, operating rate: < 60 cyc/mn,  
load factor: 0,5 conforming to IEC 60947-5-1 appendix C

## ► Fysiske mål

Materiale kropp  
contacts material

plast  
silver plated contacts

Bredde

40 mm mm

Høyde

73 mm mm

Dybde

36 mm mm

Vekt

0.08 kg kg

## ► Produktmerking

Produktspekter

OsiSense XC

Serie navn

standard størrelse

Produkt eller komponent type

limit switch body

kallenavn på utstyr

ZCKS

type kropp

fast

## Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: [kundesenter@no.schneider-electric.com](mailto:kundesenter@no.schneider-electric.com)