

H407414

Kontaktelement 1nc

Artikkelnummer: ZBE102

El-nummer: 4300424

EAN13-nummer: 3389110089486

"Trykknapper og LED lamper Ø 22mm i metall. IP66 som standard. Enkel og rask montasje. Konseptet for ""Klikk-på"" montasje er så pålitelig at bare en skrue er nødvendig for montering og den forenkler og reduserer tiden for montasje vesentlig."

Technical information

Tilleggsinformasjon

sale per indivisible quantity

5

tilleggsinformasjon

mounting on pushbutton collar

Sertifikater og standarder

Standarder

EN/IEC 60947-1

EN/IEC 60947-5-1

EN/IEC 60947-5-4

JIS C 4520

UL 508

CSA C22.2 No 14

Produktsertifikater

BV

CCC

CSA

DNV

GL

GOST

LROS (Lloyds register of shipping)

RINA

UL

Tilkoblinger

tilkoblinger - terminaler

skrutilkobling: $\leq 2 \times 1.5 \text{ mm}^2$ med endehylse conforming to EN 60947-1

skrutilkobling: $\geq 1 \times 0.22 \text{ mm}^2$ uten endehylse conforming to EN 60947-1

Elektrisk

short circuit protection

10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1

[Ith] conventional free air thermal current

10 A conforming to EN/IEC 60947-5-1

[Ui] rated insulation voltage

600 V (degree of pollution: 3) conforming to EN 60947-1

[Uimp] rated impulse withstand voltage

6 kV conforming to EN 60947-1

[le] rated operational current

3 A at 240 V, AC-15, A600 conforming to EN/IEC 60947-5-1

6 A at 120 V, AC-15, A600 conforming to EN/IEC 60947-5-1

0.1 A at 600 V, DC-13, Q600 conforming to EN/IEC 60947-5-1

0.27 A at 250 V, DC-13, Q600 conforming to EN/IEC 60947-5-1

0.55 A at 125 V, DC-13, Q600 conforming to EN/IEC 60947-5-1

1.2 A at 600 V, AC-15, A600 conforming to EN/IEC 60947-5-1

Miljø

protective treatment

TH

ambient air temperature for storage

-40...70 °C °C

ambient air temperature for operation

-25...70 °C °C

IP-grad

IP20 conforming to IEC 60529

Vibrasjonsmotstand

5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6

30 gn for 18 ms half sine wave acceleration conforming to IEC 60068-2-27

50 gn for 11 ms half sine wave acceleration conforming to IEC 60068-2-27

Praktisk

Klemmebeskrivelse ISO n°1

(11-12)NC

contacts type and composition

1 NC

contacts operation	slow-break
contacts usage	standard kontakt
Positiv åpning	med positive opening conforming to EN/IEC 60947-5-1 appendix K
operating travel	1.5 mm (NC changing electrical state) 4.3 mm (total travel)
operating force	2 N (NC changing electrical state)
electrical composition code	C1 (quantity <= 9) C2 (quantity <= 7) C3 (quantity <= 6) C4 (quantity <= 4) C5 (quantity <= 5) C6 (quantity <= 3) C7 (quantity <= 4) C8 (quantity <= 2) C9 (quantity <= 3) C12 (quantity <= 6) M1 (quantity <= 6) M2 (quantity <= 4) M3 (quantity <= 4) M5 (quantity <= 2) M6 (quantity <= 2) M7 (quantity <= 6) M8 (quantity <= 4) M9 (quantity <= 2) SF1 (quantity <= 3) SF2 (quantity <= 2) MF1 (quantity <= 2) MF2 (quantity <= 2) C10 (quantity <= 2) M4 (quantity <= 2) C13 (quantity <= 1)
 Installasjon	
montering av blokk	montering i front
 Ytelse	
mechanical durability	5000000 cycles cycles 1000000 cycles, AC-15, 2 A at 230 V, operating rate: 3600 cyc/h, load factor: 0,5 conforming to EN/IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A at 120 V, operating rate: 3600 cyc/h, load factor: 0,5 conforming to EN/IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 4 A at 24 V, operating rate: 3600 cyc/h, load factor: 0,5 conforming to EN/IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.2 A at 110 V, operating rate: 3600 cyc/h, load factor: 0,5 conforming to EN/IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.5 A at 24 V, operating rate: 3600 cyc/h, load factor: 0,5 conforming to EN/IEC 60947-5-1 appendix C $\lambda < 10\exp(-7)$ at 5 V, 1 mA in clean environment conforming to EN/IEC 60947-5-4 $\lambda < 10\exp(-8)$ at 17 V, 5 mA in clean environment conforming to EN/IEC 60947-5-4
Elektrisk levetid	
elektrisk funksjonalitet i h.h.t. IEC 60947-5-7	
 Fysiske mål	
Vekt	0.011 kg kg
Tiltrekningsmoment	0.8...1.2 N.m conforming to EN 60947-1
shape of screw head	kryss head compatible with Philips no 1 screwdriver kryss head compatible with Pozidriv No 1 screwdriver hullet head compatible with flat Ø 4 mm screwdriver hullet head compatible with flat Ø 5.5 mm screwdriver silver alloy (Ag/Ni)
contacts material	
 Produktmerking	
Produktspekter	Harmony XB4 Harmony XB5
Produkt eller komponent type	kontaktblokk
kallenavn på utstyr	ZBE

Supplier information

Leverandør: Schneider Electric Norge AS

Fax: + 47 64 98 57 01

Web: <http://www.schneider-electric.no>

Adresse: Deliveien 10, 1540 Vestby

Telefon: +47 64 98 56 00

e-Post: kundesenter@no.schneider-electric.com