



Product Groups Basket Search Delivery condition

Preinsulated terminals
Non insulated terminals
Wire end sleeves
Push on terminals
Cable ties
Screws & nuts
Electrical sockets
Cable screw glands
Enclosures
Hilsnaps
Heat shrinkable tubing
Adhesive tapes
Signs and markers

Marker
Tools
Assortments
Screwdriver & VDE Tools
Earth straps
Insulators
Main switch

HIL-BOX® enclosure system including stepped entry seals, nylon-hinged screws

Detail ARTIKEL-Nr. 55420

Shock resistant enclosures including **universal entry seals in soft material with different stepped diameters**. Cover fixed with nylon-screws. The unscrewing of the nylon screws allows to open the lid in 2 directions depending on the used screws. The screws are used as hinge and allow a fast opening of the enclosure.

protection spec.: IP 55 acc. DIN EN 60529
material: base and lid ABS (UV resistant), entry seals PVC, screws PA
colour: grey RAL 7035
installation temp.: -5°C up to +60°C acc. DIN EN 60670
temperature resistance: max. 70°C acc. DIN EN 60695-10-2
flame protection: 650°C acc. DIN EN 60695-2-11

Item Number 55420

HIL-BOX® enclosure system, universal entry seals in soft material with different stepped diameters

A [mm]	300,00
B [mm]	220,00
C [mm]	120,00
G [mm]	80,00
D [mm]	50,00
Ø diameter nipples	14 - 32
nipples	12,00

